

**XRAY T2008**

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

1

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

1

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

5.25

REAR

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3+ 4+ 3 2 1

LONG

SHORT

SHIM

1

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6.5

DOWNSTOP /mm

5

REAR

OUT

IN

0.5

SHIM UNDER SHOCK

SHIM

1

/mm

SHIM FRONT

SHIM

0

/mm

SHIM REAR

SHIM

0

/mm

TOE /deg.

FINAL TOE

2.5

OUTBOARD TOE

0.0

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

OUTBOARD + INBOARD TOE

INBOARD TOE

SHIM /mm

2.25

1.9

1.5

1.5

0.75

0.4

0

OUTER ACKERMANN POSITION

INNER ACKERMANN POSITION

SERVO SAVER

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

2

CAMBER /deg.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

5

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE /g

5

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

10

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

10

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

009 EU

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

REAR