

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

5

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3 2 1

LONG

SHORT

SHIM

2

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

5.5

DOWNSTOP/mm

4

REAR

OUT

IN

0

SHIM UNDER SHOCK

SHIM 1.15/mm

SHIM FRONT

SHIM 1.5/mm

SHIM REAR

SHIM 1.5/mm

TOE/deg.

FINAL TOE IN

3

OUTBOARD TOE

0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM /mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2.5

2.0

1.5

1.0

0.5

0

FRONT

1.5

CAMBER/deg.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE/g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE/g

BALANCE/g

CHASSIS MULTI-FLEX SETTING

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE/g

FRONT

REAR