

XRAY T2008

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

WHEELBASE /mm
☐ 0 ☒ 1 ☐ 1

DIVE
☐ +0.75 ☒ 0.00 ☐ -0.75

ROLL-CENTER
☐ +0.75 ☒ 0.00 ☐ -0.75

SHIM
☐ +0.75 ☒ 0.00 ☐ -0.75

WHEELBASE /mm
☐ 2 ☒ 1 ☐ 0

5 **RIDE HEIGHT** /mm

2 **RIDE HEIGHT** /mm

REAR

SHIM
☐ +0.75 ☒ 0.00 ☐ -0.75

WHEELBASE /mm
☐ 2 ☒ 1 ☐ 0

SHIM
☐ +0.75 ☒ 0.00 ☐ -0.75

WHEELBASE /mm
☐ 2 ☒ 1 ☐ 0

5 **RIDE HEIGHT** /mm

2 **RIDE HEIGHT** /mm

FRONT

C-HUB
☐ M ☒ H ☐ ALU

SHIM
☐ 1 /mm

STEERING BLOCK
☐ M ☒ H ☐ ALU

LONG ☒ **SHORT** ☐

UPPER SHOCK POSITION
☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

QUICK ROLL CENTER POSITION
☐ 1 ☐ 2 ☐ 3 ☐ 4

MEASURE UNDER ARM
☐ 8 ☐ 7 ☐ 6 ☐ 5 ☐ 4 ☐ 3 ☐ 2 ☐ 1 ☐ 0 ☐ -1 ☐ -2

DOWNSTOP /mm
☐ 6 ☐ 5

REAR

SHIM
☐ 1 /mm

SHIM
☐ 1 /mm

REAR HUB
☐ M ☒ H ☐ ALU

OFFSET
☒ STANDARD ☐ OTHER

MEASURE UNDER ARM
☐ 8 ☐ 7 ☐ 6 ☐ 5 ☐ 4 ☐ 3 ☐ 2 ☐ 1 ☐ 0 ☐ -1 ☐ -2

DOWNSTOP /mm
☐ 6 ☐ 5

FRONT

OUT ☒ 1 **IN** ☐ 0

SHIM UNDER SHOCK
☐ 1 /mm

SHIM FRONT
☐ 1,15 /mm

SHIM REAR
☐ 1,15 /mm

OUTER ACKERMANN POSITION
☐ 1 ☐ 2

INNER ACKERMANN POSITION
☐ 1 ☐ 2

REAR

FINAL TOE IN ☒ 2.5 **OUTBOARD TOE** ☐ 0

SHIM UNDER SHOCK
☐ 0 /mm

SHIM FRONT/REAR
☐ 1.5 mm ☒ NO shim ☐ OTHER

INBOARD TOE
☐ 2.5 ☐ 2 ☐ 1.5 ☐ 1 ☐ 0.5 ☐ 0

FRONT

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg.
☐ 2 ☐ 1.5

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg.
☐ 2 ☐ 1.5

REAR

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg.
☐ 2 ☐ 1.5

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg.
☐ 2 ☐ 1.5

FRONT

BALANCE /g
☐ 1 ☐ 0 ☐ -1

TOP DECK MULTI-FLEX SETTING
☐ US ☐ EU

ECCENTER
☒ STANDARD ☐ DIFF. POSITION

BALANCE /g
☐ 1 ☐ 0 ☐ -1

REAR

BALANCE /g
☐ 1 ☐ 0 ☐ -1

TOP DECK MULTI-FLEX SETTING
☐ US ☐ EU

ECCENTER
☒ STANDARD ☐ DIFF. POSITION

BALANCE /g
☐ 1 ☐ 0 ☐ -1

FRONT

CHASSIS
☐ US ☐ EU

CHASSIS
☐ US ☐ EU

FRONT ALU STANDS (US)
☐ BRACE (EU)

REAR ALU STANDS (US)
☐ BRACE (EU)

REAR

CHASSIS
☐ US ☐ EU

CHASSIS
☐ US ☐ EU

FRONT ALU STANDS (US)
☐ BRACE (EU)

REAR ALU STANDS (US)
☐ BRACE (EU)