

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

0

1

1

5,2

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

2

1

0

5,5

RIDE HEIGHT/mm

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3 2 1

LONG

SHORT

SHIM

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6,5

DOWNSTOP /mm

5

REAR

OUT

IN

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT

SHIM

2,25

/mm

SHIM REAR

SHIM

1,5

/mm

TOE /deg.

FINAL TOE IN

3

OUTBOARD TOE

0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2,25

1,9

1,5

1,5

0,75

0,4

0

FRONT

1,5

CAMBER /deg.

1,5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

EU 5 cell

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

REAR