

XRAY T2008

FRONT

CASTER 0° ☐ 2° ☐ 4° ☒ 6° ☐

DIVE ☐ **ROLL-CENTER** ☐

+0.75 ☒ 0.00 ☐ -0.75 ☐

SHIM 0 /mm

+0.75 ☒ 0.00 ☐ -0.75 ☐

WHEELBASE/mm 0 1 1

5 **RIDE HEIGHT**/mm

SQUAT ROLL-CENTER

+0.75 ☒ 0.00 ☐ -0.75 ☐

+0.75 ☒ 0.00 ☐ -0.75 ☐

2 1 0

RIDE HEIGHT/mm **5,2**

FRONT

C-HUB M ☒ H ☐ ALU ☐

STEERING BLOCK M ☒ H ☐ ALU ☐

OFFSET STANDARD ☒

SHIM 1 /mm

UPPER SHOCK POSITION 5 4 3 2 1

QUICK ROLL CENTER POSITION 3+ 4+ 3 2 1

LONG ☐ **SHORT** ☒

MEASURE UNDER ARM 8 7 6 5 4 3 2 1 0 -1 -2

0 1/2 **DOWNSTOP** /mm

REAR

REAR HUB M ☐ H ☐ ALU ☐

OFFSET STANDARD ☐ -0.75 ☒

SHIM 1 /mm

CAMBER LINK LOCATION 1 2

LONG ☒ **SHORT** ☐

MEASURE UNDER ARM -2 -1 0 1 2 3 4 5 6 7 8 9 10

5 **DOWNSTOP** /mm

FRONT

OUT 0.5 **IN** ☐

SHIM UNDER SHOCK SHIM 1.5 /mm

SHIM FRONT SHIM 1.5 /mm

SHIM REAR SHIM 1.5 /mm

OUTER ACKERMANN POSITION 1 2

INNER ACKERMANN POSITION 1 2

SERVO SAVER 1 2 3 4 5

REAR

FINAL TOE IN 3 **OUTBOARD TOE** 0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR SHIM 0 /mm

SHIM UNDER SHOCK SHIM 0 /mm

SHIM FRONT/REAR 1.5 mm ☐ NO shim ☒ OTHER ☐

INBOARD SHIMS SHIM /mm 2.5 ☒ 2.5 ☐ 2 ☐ 1.5 ☐ 1.5 ☐ 1 ☐ 0.5 ☐ 0 ☐

FRONT

1.5 **CAMBER** /deg.

FRONT ARM HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR

1.5 **CAMBER** /deg.

REAR ARM HARD (H) ☒ EXTRA-HARD (XH) ☐

FRONT

BALANCE /g

ECCENTER STANDARD ☒ 1 ☐

DIFF. POSITION UP ☒ DOWN ☐

BALANCE /g

REAR

BALANCE /g

ECCENTER STANDARD ☐ 1 ☐

DIFF. POSITION UP ☒ DOWN ☐

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING CHASSIS 009 6 cells

CENTRAL ALU STAND

FRONT ALU STANDS (US) **REAR ALU STANDS (US)**

BRACE (EU) ☐

REAR