

XRAY T2008

FRONT

CASTER
0° ☐ 2° ☐ 4° ☐ 6° ☒

SQUAT **ROLL-CENTER**

DIVE **ROLL-CENTER**

SHIM
0 /mm
+0.75 ☐ 0.00 ☒ -0.75 ☐

WHEELBASE/mm
0 1 1

WHEELBASE/mm
2 1 0

4.5 **RIDE HEIGHT**/mm

RIDE HEIGHT/mm **4.5**

REAR

SHIM
3mm /mm
+0.75 ☐ 0.00 ☒ -0.75 ☐

REAR HUB
M ☐ H ☒ ALU ☒

STEERING BLOCK
M ☐ H ☒ ALU ☐

UPPER SHOCK POSITION
5 4 3 2 1

LONG ☒ **SHORT** ☐

QUICK ROLL CENTER POSITION
3+ 3- 4+ 4- 1 2

MEASURE UNDER ARM
8 7 6 5 4 3 2 1 0 -1 -2

MEASURE UNDER ARM
-2 -1 0 1 2 3 4 5 6 7 8 9 10

DOWNSTOP /mm
0 1 1

DOWNSTOP /mm
0 1 1

FRONT

OUT 0 **IN**

SHIM UNDER SHOCK
SHIM /mm
SHIM FRONT
SHIM 2.5 /mm
SHIM REAR
SHIM 2.5 /mm

OUTER ACKERMANN POSITION
1 2 3 4 5

INNER ACKERMANN POSITION
1 2

TOE /deg.
FINAL TOE IN 2 **OUTBOARD TOE** 1.0

ANTI ROLL-BAR
SHIM UNDER SHOCK
SHIM /mm
SHIM FRONT/REAR
1.5 mm ☐ **NO shim** ☒ **OTHER** 2.25

SHIM /mm
2.25 = 3°
1.9 = 2.5°
1.5 = 2°
1.15 = 1.5°
0.75 ☒ = 1°
0.4 = 0.5°
0 = 0°

REAR

SHIM /mm
2.25 = 3°
1.9 = 2.5°
1.5 = 2°
1.15 = 1.5°
0.75 ☒ = 1°
0.4 = 0.5°
0 = 0°

FRONT

1.5 **CAMBER** /deg.

2.5 **CAMBER** /deg.

FRONT ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR

1.5 **CAMBER** /deg.

2.5 **CAMBER** /deg.

FRONT ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

FRONT

BALANCE /g
no

TOP DECK MULTI-FLEX SETTING
US TOP DECK
EU TOP DECK

ECCENTER /mm
STANDARD ☐ 1 ☐

DIFF. POSITION
UP ☐ DOWN ☒

BALANCE /g
no

BALANCE /g
no

REAR

BALANCE /g
no

TOP DECK MULTI-FLEX SETTING
US TOP DECK
EU TOP DECK

ECCENTER /mm
STANDARD ☐ 1 ☐

DIFF. POSITION
UP ☒ DOWN ☐

BALANCE /g
no

BALANCE /g
no

FRONT

CHASSIS MULTI-FLEX SETTING
CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)
BRACE (EU) ☐

REAR ALU STANDS (US)

REAR

CHASSIS MULTI-FLEX SETTING
CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)
BRACE (EU) ☐

REAR ALU STANDS (US)