

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

+0.75

0.00

-0.75

WHEELBASE/mm

0

1

1

5.5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

+0.75

0.00

-0.75

+0.75

0.00

-0.75

2

1

0

5.5

RIDE HEIGHT/mm

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5

4

3

2

1

LONG

SHORT

QUICK ROLL CENTER POSITION

3

4

1

2

SHIM

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

DOWNSTOP/mm

REAR

DOWNSTOP/mm

OUT

IN

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT

SHIM

/mm

SHIM REAR

SHIM

/mm

TOE / deg.

FINAL TOE IN

3.5

OUTBOARD TOE

1.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2.25

1.75

1.5

1.25

0.75

0.4

0

SHIM /mm

2.5°

2°

1.5°

1°

0.5°

0°

FRONT

1

CAMBER / deg.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

20

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE / g

10

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE / g

20

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE / g

10

FRONT

CHASSIS MULTI-FLEX SETTING

REAR

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)