

**XRAY T2008**

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

no

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

no

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

5.5

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

no

/mm

UPPER SHOCK POSITION

QUICK ROLL CENTER POSITION

LONG

SHORT

SHIM

no

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

DOWNSTOP/mm

REAR

OUT

IN

SHIM UNDER SHOCK

SHIM

2

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

1.5

/mm

TOE / degr.

FINAL TOE IN

2.5

OUTBOARD TOE

1.0

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

no

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

.75

INBOARD TOE

SHIM /mm

2.25

=3°

1.9

=2.5°

1.5

=2°

1.5

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

FRONT

CAMBER / degr.

2

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

no

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE / g

40

ECCENTER<sub>max</sub>

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE / g

no

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

REAR