

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

☒

DIVE

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

☐
☒
☐

WHEELBASE/mm

0

1

1

4.5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

☐
☒
☐

WHEELBASE/mm

2

1

0

5

RIDE HEIGHT/mm

C-HUB

M

H

ALU

☐
☒
☐

STEERING BLOCK

M

H

ALU

☐
☒
☐

OFFSET

STANDARD

☒

SHIM

1

/mm

UPPER SHOCK POSITION

5

4

3

2

1

QUICK ROLL CENTER POSITION

3+

4+

3

4

2

1

LONG

SHORT

☒
☐

SHIM

1

/mm

REAR HUB

M

H

ALU

☐
☒
☐

OFFSET

STANDARD

☐
☒

DOWNSTOP/mm

0

1

2

3

4

5

6

7

8

9

10

OUT

IN

.5

SHIM UNDER SHOCK

SHIM

2

/mm

SHIM FRONT

SHIM

2.25

/mm

SHIM REAR

SHIM

2.25

/mm

OUTER ACKERMANN POSITION

1

2

3

4

5

INNER ACKERMANN POSITION

1

2

SERVO SAVER

TOE / deg.

FINAL TOE IN

3

OUTBOARD TOE

1.0

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

☐
☒
☐

INBOARD TOE

SHIM / mm

2.25

=3°

1.9

=2.5°

1.5

=2°

1.5

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

FRONT

2

CAMBER / deg.

1

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

☒
☐

REAR ARM

HARD (H)

EXTRA-HARD (XH)

☐
☒

BALANCE / g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

☒
☐

BALANCE / g

BALANCE / g

CHASSIS MULTI-FLEX SETTING

CHASSIS

stk

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

☐

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

☒
☐

BALANCE / g