

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

+0.75

0.00

-0.75

WHEELBASE/mm

0

1

1

5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

+0.75

0.00

-0.75

2

1

0

RIDE HEIGHT/mm

5.2

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

LONG

SHORT

QUICK ROLL CENTER POSITION

0 1 2 3 4

SHIM

1

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6.2

DOWNSTOP /mm

4.8

REAR

OUT

0.5

IN

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT

SHIM

1

/mm

SHIM REAR

SHIM

1

/mm

OUTER ACKERMANN POSITION

1 2 3 4 5

INNER ACKERMANN POSITION

1 2

SERVO SAVER

TOE /degr.

FINAL TOE IN

2.5

OUTBOARD TOE

1.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2.5 = 3°

1.9 = 2.5°

1.5 = 2°

1.1 = 1.5°

0.75 = 1°

0.4 = 0.5°

0 = 0°

FRONT

1

CAMBER /degr.

1

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE /g

ECCEMTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE /g

ECCEMTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE /g

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING

REAR

CHASSIS

5 cell

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)