

XRAY T2008

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

SQUAT **ROLL-CENTER**

DIVE **ROLL-CENTER**
☒ +0.75
☐ 0.00
☐ -0.75

SHIM
☒ +0.75
☐ 0.00
☐ -0.75

WHEELBASE/mm
☒ 0 ☐ 1 ☐ 1

WHEELBASE/mm
☒ 2 ☐ 1 ☐ 0

4.8 **RIDE HEIGHT**/mm

5 **RIDE HEIGHT**/mm

REAR

C-HUB
☒ M
☐ H
☐ ALU

SHIM
☐ 1.5 /mm

STEERING BLOCK
☒ M
☐ H
☐ ALU

UPPER SHOCK POSITION
☒ LONG
☐ SHORT

QUICK ROLL CENTER POSITION
☒ LONG
☐ SHORT

CAMBER LINK LOCATION
☐ M
☐ H
☐ ALU

OFFSET
☒ STANDARD
☐ -0.75

DOWNSTOP /mm
☐ 6 ☐ 5

FRONT

OUT
☐ OUT
☐ IN

TOE /deg.
☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5

SHIM UNDER SHOCK
☐ 1.5 /mm

SHIM FRONT
☐ 1.2 /mm

SHIM REAR
☐ 1.2 /mm

OUTER ACKERMANN POSITION
☐ 1 ☐ 2

REAR

FINAL TOE IN ☐ 3 ☐ 0

OUTBOARD TOE ☐ 0

ANTI ROLL-BAR
☐ SHIM UNDER SHOCK
☐ SHIM /mm
☐ SHIM FRONT/REAR
☐ 1.5 mm
☐ NO shim
☒ OTHER .4

INBOARD TOE
☒ 2.5 = 3°
☐ 1.9 = 2.5°
☐ 1.5 = 2°
☐ 1.15 = 1.5°
☐ 0.75 = 1°
☐ 0.4 = 0.5°
☐ 0 = 0°

FRONT

1.5 **CAMBER** /deg.

1.5 **CAMBER** /deg.

FRONT ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

REAR

1.5 **CAMBER** /deg.

1.5 **CAMBER** /deg.

FRONT ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

FRONT

BALANCE /g
☐ 1

TOP DECK MULTI-FLEX SETTING
☐ US TOP DECK
☐ EU TOP DECK

ECCENTER
☐ STANDARD
☐ 1

DIFF. POSITION
☐ UP
☐ DOWN

REAR

BALANCE /g
☐ 1

TOP DECK MULTI-FLEX SETTING
☐ US TOP DECK
☐ EU TOP DECK

ECCENTER
☐ STANDARD
☐ 1

DIFF. POSITION
☐ UP
☐ DOWN

FRONT

CHASSIS
☐ CHASSIS
☐ CENTRAL ALU STAND
☐ FRONT ALU STANDS (US)
☐ REAR ALU STANDS (US)
☐ BRACE (EU)

CHASSIS
☐ CHASSIS
☐ CENTRAL ALU STAND
☐ FRONT ALU STANDS (US)
☐ REAR ALU STANDS (US)
☐ BRACE (EU)

REAR

CHASSIS
☐ CHASSIS
☐ CENTRAL ALU STAND
☐ FRONT ALU STANDS (US)
☐ REAR ALU STANDS (US)
☐ BRACE (EU)

CHASSIS
☐ CHASSIS
☐ CENTRAL ALU STAND
☐ FRONT ALU STANDS (US)
☐ REAR ALU STANDS (US)
☐ BRACE (EU)