

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

1.5

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

259

6

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

1.5

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

259

6

RIDE HEIGHT/mm

REAR

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3 2 1

LONG

SHORT

SHIM

1

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

MEASURE UNDER ARM

8 7 6 5 4 3 2 1 0 -1 -2

0

MEASURE UNDER ARM

-2 -1 0 1 2 3 4 5 6 7 8 9 10

5.2

DOWNSTOP/mm

4

FRONT

REAR

OUT

IN

.5

SHIM UNDER SHOCK

SHIM

2.5

/mm

SHIM FRONT

SHIM

1.8

/mm

SHIM REAR

SHIM

1.5

/mm

OUTER ACKERMANN POSITION

1 2

INNER ACKERMANN POSITION

1 2

TOE / deg.

FINAL TOE IN

2.5

OUTBOARD TOE

0

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

2.5

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

OUTBOARD + INBOARD TOE

INBOARD TOE

SHIM /mm

2.5

2.5°

1.5

1.5°

0.5

0.5°

0

0°

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

1.5

CAMBER / deg.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

Transponder

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

ECCEnter

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE / g

0

BALANCE / g

Reciever

ECCEnter

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE / g

Heatsink

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

2.5mm

REAR

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)