

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

1.0

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

5.5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

1.0

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

5.5

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1.0

/mm

UPPER SHOCK POSITION

QUICK ROLL CENTER POSITION

LONG

SHORT

SHIM

1.0

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

MEASURE UNDER ARM

DOWNSTOP/mm

5

4

TOE / deg.

OUT

IN

1

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

/mm

OUTER ACKERMANN POSITION

INNER ACKERMANN POSITION

SERVO SAVER

FINAL TOE IN

3

OUTBOARD TOE

1.0

INBOARD TOE

SHIM /mm

2.25

=3°

1.9

=2.5°

1.5

=2°

1.15

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

1.25

CAMBER / deg.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

1 oz

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE / g

1 oz

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE / g

1 oz

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

rubber

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

REAR