

SET-UP SHEET

XRAY T3

RACE	Basic Set-Up For Rubber Tires		
TRACK			
NAME			
CITY / COUNTRY			
CONTACT			
DATE	TEMPERATURE / °F or °C	AIR	TRACK
QUALIFYING POSITION	BEST LAPTIME / sec	FINAL POSITION	RACE LENGTH / minutes

TRACK CONDITION	☒ CARPET	☒ ASPHALT
☐ TECHNICAL	☒ MIXED	☐ FAST
TRACTION	☐ LOW	☒ MEDIUM ☐ HIGH

FRONT		REAR	
TRANSMISSION			
FRONT PULLEY	38T	38T	REAR PULLEY
☐ LOOSE ☐ MEDIUM ☐ TIGHT		☐ LOOSE ☒ MEDIUM ☐ TIGHT	
DIFF.		☒ YES ☐ NO	
ONE WAY DIFFERENTIAL		☐ YES ☐ NO	
SOLID ONE WAY DIFF.		☐ YES ☐ NO	
SOLID AXLE		☒ YES ☐ NO	
PINION / T		SPUR GEAR / T	
FINAL DRIVE RATIO		ROLLOUT	

FRONT		REAR	
☐ ALU	☒ PLASTIC	☐ ALU	☒ PLASTIC
SHOCKS			
XRAY SPRINGS			
#308393 Super Soft	☐ YELLOW	(D=1.4)	14 lb
#308384	☐ BLUE-GREEN	(D=1.5)	15 lb
#308394 Soft	☐ WHITE	(D=1.5)	17.5 lb
#308385	☐ LIGHT-BLUE	(D=1.6)	20 lb
#308395 Soft Medium	☐ BLUE	(D=1.6)	22.5 lb
#308386	☐ DARK-BLUE	(D=1.7)	25 lb
#308396 Medium	☐ VIOLET	(D=1.7)	28 lb
#308387	☐ LIGHT-PURPLE	(D=1.8)	30 lb
#308397 Medium Hard	☐ PURPLE	(D=1.8)	33 lb
#308388	☐ LIGHT-RED	(D=1.9)	35 lb
#308398 Hard	☐ RED	(D=1.9)	38 lb

#308373	☐ C 2.2	☐
#308374	☐ C 2.4	☐
#308375	☐ C 2.6	☒
#308376	☐ C 2.8	☐
#308377	☒ C 3.0	☐
#308378	☐ C 3.2	☐
#308379	☐ C 3.4	☐

OTHER SPRING	
350	350
OIL / CST	
LENGTH / mm	
PRELOAD / mm	
25%	25%
☒ YES ☐ NO	☒ YES ☐ NO
☐ YES ☒ NO	☐ YES ☒ NO

☐ OPENED	☒ CLOSED
HOLES IN PISTON	

1.4	THICKNESS / mm	ANTI-ROLL BAR	THICKNESS / mm	1.2
-----	----------------	---------------	----------------	-----

TIRES	
DIAMETER / mm	
INSERTS	
ADDITIVE	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

HUDY		WHEELS		HUDY	
S	M	☒ H	HARDNESS	S	M

MOTOR		TIMING	
ROTOR		ARMATURE	
ESC		BATTERIES	Lipo
BRUSHLESS	PROGRAM	PUNCH	INITIAL BRAKE
BODY		WING	

FRONT		SQUAT		ROLL-CENTER		REAR	
CASTER	0° ☐ 2° ☐ 4° ☒ 6° ☐	SHIM	0 / mm	+0.75 ☐ 0.00 ☒ -0.75 ☐	SHIM	0 / mm	+0.75 ☐ 0.00 ☒ -0.75 ☐
DIVE	+0.75 ☐ 0.00 ☒ -0.75 ☐	SHIM	0 / mm	SHIM	0 / mm	SHIM	0 / mm
WHEELBASE / mm	5		RIDE HEIGHT / mm		5.2		

FRONT		REAR	
C-HUB	M ☒ H ☐ ALU ☐	SHIM	1 / mm
STEERING BLOCK	M ☒ H ☐ ALU ☐	SHIM	4 / mm
OFFSET	STANDARD ☒	REAR HUB	M ☒ H ☐ ALU ☐
DOWNSTOP / mm	6	DOWNSTOP / mm	5

TOE / degr.	FINAL TOE IN	3	OUTBOARD TOE	0
OUT	1	INBOARD TOE	SHIM / mm	
SHIM UNDER SHOCK	SHIM 0 / mm	SHIM UNDER SHOCK	SHIM 0 / mm	
SHIM FRONT	SHIM 1.5 / mm	SHIM FRONT/REAR	NO shim ☒ OTHER ☐	
SHIM REAR	SHIM 1.5 / mm			

FRONT		CAMBER / degr.		REAR	
-2	-1.5	UPPER SHOCK POSITION		REAR ARM	HARD (H) ☒ EXTRA-HARD (XH) ☐
REAR ARM	HARD (H) ☒ EXTRA-HARD (XH) ☐	REAR ARM	HARD (H) ☒ EXTRA-HARD (XH) ☐		

FRONT		TOP DECK MULTI-FLEX SETTING		REAR	
ALU ORAL	OPTIONAL	EU TOP DECK		ECCENTER	STANDARD ☒
ECCENTER	STANDARD ☒	US TOP DECK		DIFF. POSITION	UP ☒ DOWN ☐

BALANCE / g	20	BATTERIES TYPE	5-CELL ☐ 6-CELL ☐ LIPO ☒	BALANCE / g	10
RIGHT	☒	BATTERIES POSITION	OUTSIDE ☒ INSIDE ☐	LEFT	☐
FRONT BELT POSITION	LEFT				
BALANCE / g				BALANCE / g	