

XRAY T3

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

SHIM

0

/mm

5

RIDE HEIGHT/mm

WHEELBASE/mm

0

1

1

SQUAT

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

SHIM

0

/mm

2

1

0

RIDE HEIGHT/mm

5

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

+75

SHIM

2

/mm

LONG 52

SHORT 50

QUICK ROLL CENTER POSITION

MEASURE UNDER ARM

DOWNSTOP /mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

-75

SHIM

3

/mm

LONG 52

SHORT 50

CAMBER LINK LOCATION

OPTIONAL HUB

MEASURE UNDER ARM

DOWNSTOP /mm

TOE /degr.

FINAL TOE IN

1

OUTBOARD TOE

1.0

OUT

IN

SHIM UNDER SHOCK

SHIM

1

/mm

SHIM FRONT

SHIM

2.25

/mm

SHIM REAR

SHIM

2.25

/mm

1 2 3 4 5

1 2

ACKERMANN POSITION

INNER ACKERMANN POSITION

SERVO SAVER

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

NO shim

OTHER

.75

OUTBOARD + INBOARD TOE

INBOARD TOE

SHIM /mm

1.9

1.5

1.15

0.75

0.4

0

3.5°

3°

2.5°

2°

1.5°

1°

FRONT

2

CAMBER /degr.

2

REAR

UPPER SHOCK POSITION

REAR ARM

HARD (H)

EXTRA-HARD (XH)

5 4 3 2 1

1 2 3 4 5

OPTIONAL ARM

FRONT

ALU BRACE

OPTIONAL

ECCENTER

STANDARD

1

DIFF. POSITION

UP

DOWN

TOP DECK MULTI-FLEX SETTING

EU TOP DECK

US TOP DECK

ECCENTER

STANDARD

1

DIFF. POSITION

UP

DOWN

FRONT

BALANCE /g

0

BATTERIES TYPE

5-CELL

6-CELL

LIPO

BATTERIES POSITION

OUTSIDE

INSIDE

RIGHT

FRONT BELT POSITION

LEFT

BALANCE /g

0

FRONT

REAR