

SET-UP SHEET

RACE			
TRACK			
NAME			
CITY / COUNTRY			
CONTACT			

DATE		TEMPERATURE / °F or °C	AIR	TRACK
------	--	------------------------	-----	-------

QUALIFYING POSITION	BEST LAP TIME / sec	FINAL POSITION	RACE LENGTH / minutes
---------------------	---------------------	----------------	-----------------------

TRACK CONDITION	☐ CARPET	☐ ASPHALT	
☐ TECHNICAL	☐ MIXED	☐ FAST	
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

FRONT	REAR
TRANSMISSION	

SOLID AXLE	☐ YES	BALL DIFFERENTIAL	☐ YES
SOLID ONE WAY DIFF.	☐ YES		
ONE WAY DIFFERENTIAL	☐ YES		

GEAR DIFFERENTIAL	☐ YES	GEAR DIFFERENTIAL	☐ YES
OIL		OIL	/Cst

PINION / T		SPUR GEAR / T	
FINAL DRIVE RATIO		ROLLOUT	

FRONT	REAR
-------	------

	XRAY SPRINGS	
	OIL / CST	
	LENGTH / mm	
	PRELOAD / mm	
	REBOUND %	

☐ YES	☐ NO	FOAM INSERTS	☐ YES	☐ NO
☐ YES	☐ NO	O-RING ON SHAFT	☐ YES	☐ NO

☐ 3 HOLES	PISTONS	☐ 3 HOLES
☐ 4 HOLES	1.0mm	☐ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm
--------------	---------------	--------------

	TIRES	
	INSERTS	
	ADDITIVE	
	ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

	WHEELS	
S ☐	M ☐	H ☐
	HARDNESS	S ☐
		M ☐
		H ☐

MOTOR		TIMING	
ROTOR		ARMATURE	

ESC		BATTERIES	
-----	--	-----------	--

BODY		WING	
------	--	------	--

☐ - APPLIED	S - SOFT	M - MEDIUM	H - HARD
------------------------------------	----------	------------	----------

XRAY T4'14

FRONT	REAR
CASTER 0° ☐ 2° ☐ 4° ☐ 6° ☐	
SHIM /mm	
WHEELBASE/mm	
RIDE HEIGHT/mm	RIDE HEIGHT/mm

C-HUB	SHIM /mm	LONG 52mm ☐	SHIM /mm	SHIM /mm	LONG 52mm ☐	SHIM /mm	REAR HUB
M ☐		SHORT 50mm ☐			SHORT 50mm ☐		M ☐
H ☐							H ☐
ALU ☐							ALU ☐
STEERING BLOCK							
M ☐							
H ☐							
ALU ☐							
OFFSET							OFFSET
STANDARD ☐							STANDARD ☐
FRONT	DOWNSTOP /mm						REAR

FF	FR	RR	RF
FF	FR	RR	RF
ROLL CENTER ECCENTRIC BUSHINGS			

TOE /deg.	FINAL TOE IN OUTBOARD + INBOARD TOE	OUTBOARD TOE
TOE OUT		
SHIM UNDER SHOCK	ACKERMANN SHIM	SHIM UNDER SHOCK
SHIM /mm	SHIM /mm	SHIM /mm
STEERING ARM		
STANDARD ☐		
ALU ☐		
ROLL CENTER UPPER CLAMP		ROLL CENTER UPPER CLAMP

FRONT	REAR
CAMBER /deg.	
UPPER SHOCK POSITION	
FRONT ARM	REAR ARM
STANDARD (H) ☐	STANDARD (H) ☐
GRAPHITE (G) ☐	GRAPHITE (G) ☐
GRAPHITE PLATE	GRAPHITE PLATE
YES ☐	YES ☐
NO ☐	NO ☐
FRONT	REAR

BALANCE /g	TOP DECK	BALANCE /g
	2.0mm ☐	
	1.6mm ☐	
ECCENTER /mm		ECCENTER /mm
STANDARD ☐		STANDARD ☐
1 ☐		1 ☐
DIFF POSITION		DIFF POSITION
UP ☐		UP ☐
DOWN ☐		DOWN ☐
LOWER SUSP. BLOCK		LOWER SUSP. BLOCK
SOLID 1pcs ☐		SOLID 1pcs ☐
SINGLE 2 pcs ☐		SINGLE 2 pcs ☐
BALANCE /g	BALANCE /g	BALANCE /g
ALU STAND		ALU STAND
YES ☐		YES ☐
NO ☐		NO ☐

COMMENTS
