

SET-UP SHEET

XRAY T4'15

RACE	European Spec Championship		
TRACK	Torres Novas		
NAME	Delorme Pierre		
CITY / COUNTRY	Montbrison	France	
CONTACT	delormerc@hotmail.fr		

DATE	29/08/2015	TEMPERATURE / °F or °C	AIR	35	TRACK	50
------	------------	------------------------	-----	----	-------	----

QUALIFYING POSITION	BEST LAP TIME /sec	FINAL POSITION	RACE LENGTH /minutes
5th	15.4	3rd	5

TRACK CONDITION	☒ TECHNICAL	☐ CARPET	☒ ASPHALT
	☐ LOW	☒ MEDIUM	☐ FAST
TRACTION	☐ HIGH		

FRONT	REAR
TRANSMISSION	

SOLID AXLE	☒ YES	BALL DIFFERENTIAL	☐ YES
SOLID ONE WAY DIFFERENTIAL	☐ YES		
ONE WAY DIFFERENTIAL	☐ YES		

GEAR DIFFERENTIAL	☐ YES	GEAR DIFFERENTIAL	☒ YES
OIL	/Cst	OIL	10K /Cst

PINION / T	31	SPUR GEAR / T	78
FINAL DRIVE RATIO	4.7806	ROLLOUT	

FRONT	REAR
-------	------

Kit	SHOCK TYPE	Kit
2.7	XRAY SPRINGS	2.6
550	OIL /Cst	550
0	REBOUND %	0

☒ YES	☐ NO	FOAM INSERTS	☒ YES	☐ NO
☐ YES	☒ NO	O-RING ON SHAFT	☐ YES	☒ NO

☐ 3 HOLES	PISTONS	☐ 3 HOLES
☐ 4 HOLES	1.0mm	☐ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Controlled tires	TIRES
MR33	INSERTS
50	ADDITIVE
	ADDITIVE TIMING

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

ECCENTRIC BUSHINGS	ROLL CENTER	ECCENTRIC BUSHINGS
FF	1 ☒ 0.5 ☐ 1 ☐	RR
FRR	1 ☐ 0.5 ☒ 1 ☐	RF

MOTOR	Trinity D4 Certified	TIMING	58?
-------	----------------------	--------	-----

ESC	Orca VXX	BATTERIES	Trinity
-----	----------	-----------	---------

BODY	LTGR-R	WING	Light
------	--------	------	-------

COMMENTS

FRONT	REAR	
CASTER	0° ☐ 2° ☐ 4° ☒ 6° ☐	
SHIM	3 /mm	
WHEELBASE /mm	256	
5.1	5.3	

C-HUB	SHIM	DRIVE SHAFT	SHIM	SHIM	DRIVE SHAFT	SHIM	REAR HUB
M ☒	2 /mm	LONG 52mm ☒	0 /mm	/mm	LONG 52mm ☒	/mm	M ☐
H ☐		SHORT 50mm ☐			SHORT 50mm ☐		H ☐
G ☐							G ☐
ALU ☐							ALU ☐
STEERING BLOCK							
M ☐							
H ☒							
ALU ☐							
OFFSET							OFFSET
STANDARD ☒							STANDARD ☒
5.6	DOWNSTOP /mm	4.8					

ARS ACTIVE REAR SUSPENSION™	SHIM	SHIM	STEERING BLOCK
	0 /mm	1.5 /mm	M ☐
			H ☐
			ALU ☐
	SHIM	SHIM	OFFSET
	1mm /mm	Up /mm	STANDARD ☐

TOE OUT	0	TOE /deg.	FINAL TOE IN	2.75	OUTBOARD TOE	1.25
LOWER	0 /mm					
UPPER	4 /mm					
ACKERMANN SHIM	0 /mm					
STEERING ARM	STANDARD ☒					
STEERING POST	YES ☐ NO ☒					
STEERING PLATE	YES ☐ NO ☒					
MOTOR MOUNT	STANDARD ☒					
MOTOR MOUNT FLEX	YES ☐ NO ☒					
ALU STAND	YES ☐ NO ☒					
SHIMS UNDER SHOCK	2 /mm					
SHIMS UNDER SHOCK	2 /mm					

FRONT ARM	STANDARD (H) ☐	GRAPHITE (G) ☒	GRAPHITE PLATE	YES ☐ NO ☒
REAR ARM	STANDARD (H) ☐	GRAPHITE (G) ☒	GRAPHITE PLATE	YES ☐ NO ☒

DIFF. POSITION	UP ☒	DOWN ☐	DIFF. POSITION	UP ☒	DOWN ☐
LOWER SUSP. BLOCK	SOLID 1pcs ☒	SINGLE 2pcs ☐	LOWER SUSP. BLOCK	SOLID 1pcs ☐	SINGLE 2pcs ☒