

SET-UP SHEET

XRAY T4

RACE	Snowbird Nationals		
TRACK	Worldgate Resort		
NAME	Alexander Hagberg		
CITY / COUNTRY	Orlando	USA	
CONTACT	alexander.hagberg@gmail.com		

DATE	04/02/2013	TEMPERATURE / °F or °C	AIR	TRACK
QUALIFYING POSITION	1	BEST LAPTIME /sec	10.3	RACE LENGTH /minutes
		FINAL POSITION	1	5

TRACK CONDITION	☒ CARPET	☐ ASPHALT
	☐ TECHNICAL	☐ FAST
TRACTION	☐ LOW	☒ MEDIUM
	☐ HIGH	

FRONT	REAR
TRANSMISSION	
SOLID AXLE ☒ YES	BALL DIFFERENTIAL ☐ YES
SOLID ONE WAY DIFF. ☐ YES	
ONE WAY DIFFERENTIAL ☐ YES	
GEAR DIFFERENTIAL ☐ YES	GEAR DIFFERENTIAL ☒ YES
OIL	OIL 2000 /Cst

PINION / T	24	SPUR GEAR / T	112
FINAL DRIVE RATIO	4.6666666666667	ROLLOUT	NaN

FRONT	REAR
2.5-2.8	XRAY SPRINGS 2.5
350	OIL / CST 350
	LENGTH /mm
	PRELOAD /mm
0	REBOUND % 0

☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO
☐ YES ☒ NO	O-RING ON SHAFT	☐ YES ☒ NO

☐ 3 HOLES ☒ 4 HOLES	PISTONS 1.0mm 1.1mm 1.2mm OTHERS	☐ 3 HOLES ☒ 4 HOLES
---	--	---

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Jaco Blue	TIRES	Jaco Blue
	INSERTS	
SXT	ADDITIVE	SXT
15	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

WHEELS			
S ☐	M ☐	H ☐	HARDNESS
S ☐	M ☐	H ☐	

MOTOR	ORCA TX 4.5T	TIMING	STD
ROTOR	12.5	ARMATURE	
ESC	ORCA VX	BATTERIES	ORCA INFINITE
BODY	Speed 6 LW	WING	MR33

● ☒ - APPLIED S-SOFT M-MEDIUM H-HARD

FRONT	REAR
CASTER 0° ☐ 2° ☐ 4° ☒ 6° ☐ DIVE +0.75 ☐ 0.00 ☒ -0.75 ☐ ROLL-CENTER SHIM 1 /mm SHIM 2 /mm WHEELBASE/mm 258 RIDE HEIGHT/mm 5	SQUAT +0.75 ☐ 0.00 ☒ -0.75 ☐ ROLL-CENTER SHIM 4 /mm LONG 52mm ☒ SHORT 50mm ☒ CAMBER LINK LOCATION RIDE HEIGHT/mm 5.3

FRONT	REAR
C-HUB M ☒ H ☐ ALU ☐ STEERING BLOCK M ☐ H ☒ ALU ☐ OFFSET STANDARD ☒ MEASURE UNDER ARM DOWNSTOP /mm 6.4	REAR HUB M ☒ H ☐ ALU ☐ OFFSET STANDARD ☒ MEASURE UNDER ARM DOWNSTOP /mm 4.6

TOE /deg.	FINAL TOE IN 3	OUTBOARD TOE 0	INBOARD TOE
OUT 2			SHIM /mm
IN			1 = 3.5°
			0.75 = 3°
			0.5 = 2.5°
			0 = 2°

FRONT	REAR
CAMBER /deg. 2 UPPER SHOCK POSITION FRONT ARM HARD (H) ☐ EXTRA-HARD (XH) ☐ GRAPHITE (G) ☒ OPTIONAL ARM	CAMBER /deg. 1.5 UPPER SHOCK POSITION REAR ARM HARD (H) ☐ EXTRA-HARD (XH) ☐ GRAPHITE (G) ☒ OPTIONAL ARM

ECCENTER /mm STANDARD ☒ 1 ☐ DIFE POSITION UP ☒ DOWN ☐ LOWER SUSP. BLOCK SOLID 1pcs ☒ SINGLE 2 pcs ☐	BALANCE /g 10 MOTOR HOLDER STANDARD ☐ OPTION ☒ BALANCE /g 5 BALANCE /g 5	ECCENTER /mm STANDARD ☒ 1 ☐ DIFE POSITION UP ☐ DOWN ☒ LOWER SUSP. BLOCK SOLID 1pcs ☐ SINGLE 2 pcs ☒
---	--	---

COMMENTS