

SET-UP SHEET

XRAY X10'18

RACE	Basic CARPET Set-Up	
TRACK		
NAME		DATE
TEMPERATURE AIR		TEMPERATURE TRACK
RACE LENGTH	/min	BEST LAP TIME
QUALIFYING POSITION		FINAL POSITION

TRACK	
TRACK SURFACE	☒ CARPET ☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL ☒ MIXED ☐ FAST
TRACTION	☐ LOW ☒ MEDIUM ☐ HIGH

CENTER SHOCK ABSORBER	
CENTER SHOCK OIL	700 /cSt
CENTER SHOCK REBOUND	50 %
CENTER SHOCK SPRING ☐ SILVER C=1.5 ☒ GOLD C=1.8 ☐ BLACK C=2.1 ☐ BLACK C=1.4-1.9 ☐ BLACK C=2.0-2.5	

SIDE DAMPING	
SIDE TUBE	OIL 10K /cSt

FRONT	TIRES	REAR
	TIRES TYPE	
56	DIAMETER /mm	58
	ADDITIVE	
	ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
ADDITIVE TREATED AREA			

TRANSMISSION	
DIFF SETTING	
☐ LOOSE ☒ ☐ MEDIUM ☐ TIGHT	

GEARING	
PINION / T	SPUR GEAR/T 96
FINAL DRIVE RATIO	ROLLOUT

ELECTRONICS	
MOTOR	
SPEEDO	
BATTERIES	

BODY	
TYPE	

COMMENTS

Ride height is directly affected by tire diameter. This basic set-up is intended for medium tire sizes. When smaller or larger diameter tires are used, the ride height must be changed as appropriate.

