

SET-UP SHEET

XRAY X12'15

RACE	Hot Race Winter Shootout	
TRACK	G.Racing Mini Circuito Chiari	

NAME	Alexander Hagberg	
CITY / COUNTRY	Chiari	Italy
CONTACT	alexander.hagberg@gmail.com	

DATE	19/01/2015	
TEMPERATURE / <small>F or °C</small>	AIR	TRACK

QUALIFYING POSITION	BEST LAPTIME / sec	FINAL POSITION	RACE LENGTH / minutes
1	9.8	1	5

TRACK CONDITION	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input checked="" type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

CENTER SHOCK ABSORBER			
SPRING	Gold	OIL / cSt	500
		REBOUND %	25

SIDE LINKAGES	<input checked="" type="checkbox"/>	OIL / cSt	10.000
SIDE SHOCK	<input type="checkbox"/>	OIL / cSt	

FRONT		TIRES	REAR	
Hot Race EC			Hot Race EC	
41	DIAMETER/mm		42.5	
Spider green	ADDITIVE		Spider green	
1 hr	ADDITIVE timing		1 hr	

FRONT LEFT	FRONT RIGHT	ADDITIVE TREATED AREA	REAR LEFT	REAR RIGHT

TRANSMISSION			
DIFF SETTING			
<input type="checkbox"/> LOOSE	<input type="checkbox"/>	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT

PINION / T	27	SPUR GEAR/T	96
FINAL DRIVE RATIO	3.5556	ROLLOUT	37.532

ELECTRONICS	
MOTOR	ORCA TX 4.0T
SPEEDO	ORCA VX3 1S
BATTERIES	ORCA 6800 90C

BODY	PF AMR-12
-------------	-----------

FRONT	SHOCK POSITION	SHOCK ABSORBER	REAR
	FORWARD <input checked="" type="checkbox"/> ← → REARWARD <input type="checkbox"/>		
	SHIMS	DROOP	
	4.5 /mm 2 /mm	/mm	
	RIDE HEIGHT /mm	MID RIDE HEIGHT /mm	RIDE HEIGHT /mm
	3.5	3.8	4

FRONT	REAR
CASTER	RIDE HEIGHT
2mm <input checked="" type="checkbox"/> 1mm <input type="checkbox"/> 0.5mm <input type="checkbox"/> 0mm <input type="checkbox"/>	
REACTIVE CASTER	SIDE SPRING
RIDE HEIGHT WASHER	
0.5 /mm	

FRONT	FRONT	REAR
TRACK WIDTH	CAMBER / degr.	
RIGHT: 0 <input checked="" type="checkbox"/> 0.5 <input type="checkbox"/> -0.5 <input type="checkbox"/> -1 <input type="checkbox"/> LEFT: 0 <input type="checkbox"/> -0.5 <input type="checkbox"/> -1 <input type="checkbox"/> +0.5 <input type="checkbox"/> +1 <input type="checkbox"/>	0 LEFT 0 RIGHT	
SHIMS		
1 /mm		
SHIMS		
1 /mm		
SHIMS		
/mm		
LUBE		
7000 /cSt		
SPRINGS		
<input type="checkbox"/> GOLD C=3.5 <input type="checkbox"/> SILVER C=4.0 <input type="checkbox"/> BLACK C=5.0 <input type="checkbox"/> GREY C=6.0		
OTHER AE .018		

TOE / degr.	SERVO POSITION	BATTERY POSITION	SHIMS
OUT 1	RIGHT <input checked="" type="checkbox"/> LEFT <input type="checkbox"/>	INLINE <input type="checkbox"/> CROSS CHASSIS <input checked="" type="checkbox"/>	0 /mm
ACKERMANN			
SHIMS 0 /mm			
SHIMS			
/mm			
FRONT WIDTH SHIM	LINKAGE POSITION	CHASSIS	REAR WIDTH
1 /mm	2 1 2	STANDARD <input checked="" type="checkbox"/> OTHER	169 /mm

COMMENTS Front droop 0.5mm