

XRAY X4F'23

Arn0 - PetitRC

FRONT & REAR SUSPENSION

FRONT CASTER: 5°, 4°, 3°. Adjust with eccentric bushings.

BUMP STEER: /mm

HEIGHT: /mm

SHIM: /mm

TOE GAIN: /mm

REAR CASTER: 0.5°, 1.5°, 2.5°, 3.5°, 4.5°, 5.5°. Adjust with eccentric bushings.

FF: /mm

RIDE HEIGHT: /mm

FR: /mm

SERVO SAVER: YES ☐ NO ☐

SERVO HORN: YES ☐ NO ☐

RF: /mm

RIDE HEIGHT: /mm

RR: /mm

CAMBER: /degr. Left = Right

BODY STOP: YES ☐ NO ☐ /mm

FRONT SUSPENSION

FRONT BRACE: YES ☐ NO ☐

BULKHEAD SHIMS: YES ☐ 3mm ☐ NO ☐

FRONT SHOCK POSITION: 1 2 3 4

FRONT HUB: COMPOSITE ☐ ALU ☐

SHIM: /mm

DRIVE SHAFT: 58mm ☐ 59mm ☐ STD. BEARING ☐

DOWNSTOP: /mm

REAR SUSPENSION

SHIM: /mm

REAR SHOCK POSITION: 1 2 3 4

REAR HUB: COMPOSITE ☐ ALU ☐

SHIM: /mm

DOWNSTOP: /mm

FRONT TOP VIEW

TOE OUT: Left = Right

ACKERMANN: SHIM /mm

SHIM: /mm

TOE IN: Left = Right

DIFF POSITION: UP ☐ DOWN ☐

UPPER ARM: STANDARD ☐

STEERING BRIDGE: YES ☐ NO ☐

OFFSET: STANDARD ☐ -0.5mm ☐ SHIM/mm

TOP DECK: STANDARD ☐ SPLITTED ☐

BRASS WEIGHT FOR MOTOR MOUNT

TOP DECK FLEX

TOP DECK CUTTING

FRONT BOTTOM VIEW

STEER. LOCK: /degr.

STEER. SHIM: SIZE /mm

FRONT BRACE: YES ☐ NO ☐

MOTOR MOUNT

T-BRACE: ALU ☐ BRASS ☐

CHASSIS T-BRACE

FRONT ARMS: MEDIUM ☐ HARD ☐

STEER. PLATE: STANDARD ☐ +1mm ☐

GRAPHITE

REAR ARMS: MEDIUM ☐ HARD ☐