

SET-UP SHEET

X4F'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'26

RACE		
TRACK		
NAME		DATE

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAP TIME	LAPS	TIME
			/sec	/	

TRACK		
TRACK SURFACE	☐ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED ☐ FAST
TRACTION	☐ LOW	☐ MEDIUM ☐ HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL /cSt		
PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
XRAY SPRINGS		
OIL /cSt		
REBOUND %		
☐ 4 HOLES ☐ PSS	1.1mm 1.2mm	1.1mm 1.2mm ☐ 4 HOLES ☐ PSS
SHOCK LENGTH /mm		SHOCK LENGTH /mm

THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm

Timing:	Temp.:	TIRE ADDITIVE	Timing:	Temp.:
		ADDITIVE TIMING		
		WIPE OFF TIME		
		TIRE WARMERS		

SIDE WALL GLUE	FRONT TIRES
DIA. /mm	ADDITIVE AREA /mm

TOTAL WEIGHT /g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR	TIMING	RPM LIMIT	
ESC	BATTERIES		
BODY	WING		

	BODY POSITION Dimension from body post to window bottom line /mm WING SIDE PLATE YES ☐ NO ☐ Dimension from body post to upper holder /mm Dimension from edge to surface /mm
--	---

	TOP DECK CUTTING 2.0mm ☐ 1.6mm ☐ TOP DECK FLEX TOP DECK CUTTING
--	--

FRONT ARMS	CHASSIS	REAR ARMS
MEDIUM ☐ HARD ☐ GRAPHITE ☐	GRAPHITE ☐ ALU ☐	MEDIUM ☐ HARD ☐ GRAPHITE ☐

FRONT CASTER	Upper links CASTER	FRONT & REAR SUSPENSION	REAR CASTER	Upper links CASTER
5° 4° 3° Adjust with eccentric bushings		BUMP STEER /mm HEIGHT /mm SHIM /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings	
/mm FF RIDE HEIGHT	/mm FR RIDE HEIGHT	SERVO SAVER SERVO HORN	/mm RF RIDE HEIGHT	/mm RR RIDE HEIGHT

CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
/degr. Left = Right	YES ☐ NO ☐ /mm	SHOCK HOLDERS SHIM /mm SUSPENSION FLEX YES ☐ NO ☐	MEDIUM ☐ HARD ☐ GRAPHITE ☐ ALU ☐ SHIM /mm
	DRIVE SHAFT 58mm 59mm BEARING BLADE	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐

CAMBER	SHOCK HOLDERS	REAR SUSPENSION	REAR HUB
/degr. Left = Right	FIXED ☐ ACTIVE ☐ SHIM /mm	SHOCK HOLDERS SHIM /mm SUSPENSION FLEX YES ☐ NO ☐	MEDIUM ☐ HARD ☐ GRAPHITE ☐ ALU ☐ SHIM /mm
	#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐	

TOE OUT	TOE IN	FRONT TOP VIEW	REAR
Left = Right	Left = Right	DIFF POSITION UP ☐ +1mm ☐ DOWN ☐ STD. ☐	ARS LINKS SHIMS /mm
		SHIMS /mm Battery weight plate.	REAR UPPER ARM LINKS C ☐ XS ☐ S ☐ M ☐
HUB OFFSET ☐ SHIM /mm	HUB OFFSET ☐ SHIM /mm	ACKERMANN BUSHINGS	

WEIGHT LEFT & RIGHT	STEER. LOCK	T-BRACE	FRONT BOTTOM VIEW	REAR
#309826 YES ☐ NO ☐	/degr.	ALU ☐ BRASS ☐	BUMPER WEIGHT YES ☐ NO ☐	MOTOR MOUNT YES ☐ FRONT BRACE ☐ NO ☐
		CHASSIS T-BRACE	CHASSIS GRAPHITE ☐ ALU ☐	REAR ARMS MEDIUM ☐ HARD ☐ GRAPHITE ☐

COMMENTS