

SET-UP SHEET

X4F'27 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'27

RACE	Basic - Low Grip - Carpet		
TRACK			
NAME		DATE	
COUNTRY		CITY	

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAP TIME	LAPS	TIME
			/sec		/

TRACK		
TRACK SURFACE	☒ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☒ MIXED
TRACTION	☒ LOW	☐ MEDIUM
	☐ HIGH	

TRANSMISSION		
GEAR DIFFERENTIAL - OIL	500K /cSt	DIFFERENTIAL POSITION UP ☐ DOWN ☒
PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
BEARING HOLDER KIT		☒ KIT ☐ ALU

FRONT	SHOCKS	REAR
2,6/2,9	XRAY SPRINGS	2,7
350	OIL /Cst	350
REBOUND %		
☒ 4 HOLES	☒ 1.1mm	☒ 4 HOLES
☐ PSS	☐ 1.2mm	☐ PSS
SHOCK LENGTH	7 /mm	SHOCK LENGTH
		8,5 /mm

1,2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1,2
-----	--------------	---------------	--------------	-----

TIRES	
ADDITIVE	
ADDITIVE TIMING	
WIPE OFF TIME	
TIRE WARMERS	
Timing:	Temp.:
SIDE WALL GLUE DIA. /mm FRONT TIRES ADDITIVE AREA /mm	

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
--------------	----	----------------	---------	--------

MOTOR	TIMING	RPM LIMIT
ESC	BATTERIES	
BODY	WING	

BODY POSITION	
Dimension from body post to window bottom line	
/mm	
WING SIDE PLATE YES ☐ NO ☐	
Dimension from body post to upper holder	
/mm	
Dimension from edge to surface	
/mm	

FRONT REINFORCEMENT	TOP DECK FLEX	REAR REINFORCEMENT	TOP DECK CUTTING
☒	☐	☐	☐

COMMENTS	
----------	--

FRONT CASTER		5 Upper links CASTER		FRONT & REAR SUSPENSION		REAR CASTER		2,5 Upper links CASTER	
☒ 5°	☐ 4°	☐ 3°				☒ 0.5°	☐ 1.5°	☐ 2.5°	☐ 3.5°
Adjust with eccentric bushings						Adjust with eccentric bushings			
BUMP STEER		HEIGHT		SHIM		TOE GAIN		3 /mm	
1 /mm		/mm		/mm		/mm		/mm	
FRIDE HEIGHT		FR 1 /mm		☐ SERVO SAVER		RRIDE HEIGHT		RR 1,5 /mm	
☒		☒		☒		☒		☒	

FRONT	
2 /deg.	CAMBER
Left=Right	
BODY STOP YES ☒ NO ☐	
SHIM /mm	
3	
PLAY /mm	
0	
FF 1 SHIMS /mm	
FR 1 2	
FRONT HUB	
MEDIUM ☐ GRAPH. ☐	
HARD ☒ ALU ☐	
#107730 Droop Gauge	
DRIVE SHAFT	
SHIM /mm	
0,5	
23,4 DROOP /mm	
Set with shocks ☐ Set without shocks ☐	
SUSPENSION FLEX SCREW	
YES NO YES NO	
58mm 59mm	

REAR	
2 /deg.	CAMBER
Left=Right	
SHIM /mm	
3	
PLAY /mm	
0	
RF 1 SHIMS /mm	
RR 1 2	
REAR HUB	
MEDIUM ☐ GRAPH. ☐	
HARD ☒ ALU ☐	
SHIM /mm	
1	
22,6 DROOP /mm	
Set with shocks ☒ Set without shocks ☐	
SUSPENSION FLEX SCREW	
YES NO YES NO	

FRONT TOP VIEW		REAR	
1 TOE OUT		3 TOE IN	
Left=Right		Left=Right	
BUMPER WEIGHT		ARS LINKS POSITION	
YES ☒ NO ☐			
UPPER CLAMP KIT ☒ -1mm			
SHIMS /mm			
UPPER CLAMP FLEX		UPPER CLAMP FLEX	
FRONT UPPER		CHASSIS FLEX	
CFF™ ARM ☐		NO BRACE ☐	
LINK SHORT ☒		MEDIUM ☐	
LINK LONG ☐		STIFF ☒	
HUB OFFSET ☒		HUB OFFSET ☒	
SHIM /mm		SHIM /mm	
ACKERMANN BUSHINGS		ACKERMANN BUSHINGS	

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT #30926		STEER. LOCK	
YES ☒ NO ☐		25 /deg.	
FRONT BRACE		MOTOR MOUNT	
T-BRACE		T-BRACE	
ALU ☐		BRASS ☐	
FRONT ARMS		CHASSIS	
MEDIUM ☐		GRAPHITE ☒	
HARD ☐		ALU 1.5 ☐	
SHORT ☒		REAR ARMS	
		MEDIUM ☐	
		HARD ☐	
		SHORT ☒	
		reset all	