

SET-UP SHEET

RACE	ETS Round 1		
TRACK	Hrotovice		
NAME	Marco Kaufmann		
CITY / COUNTRY	Czech republic	Germany	
CONTACT			

DATE	13/11/2013	TEMPERATURE / °F or °C	AIR	TRACK
------	------------	------------------------	-----	-------

QUALIFYING POSITION	BEST LAP TIME /sec	FINAL POSITION	RACE LENGTH /minutes
	12.0		

TRACK CONDITION	☒ CARPET	☐ ASPHALT	
☒ TECHNICAL	☐ MIXED	☐ FAST	
TRACTION	☐ LOW	☐ MEDIUM	☒ HIGH

FRONT	REAR
TRANSMISSION	

SOLID AXLE	☐ YES	BALL DIFFERENTIAL	☐ YES
SOLID ONE WAY DIFF.	☐ YES		
ONE WAY DIFFERENTIAL	☐ YES		

GEAR DIFFERENTIAL	☐ YES	GEAR DIFFERENTIAL	☒ YES
OIL	2.5 Million	OIL	2000 /Cst

PINION / T	18	SPUR GEAR / T	116
FINAL DRIVE RATIO	12.24	ROLLOUT	0

FRONT	REAR
-------	------

2.5-2.8	XRAY SPRINGS	2.6
---------	--------------	-----

350	OIL / CST	350
-----	-----------	-----

	LENGTH /mm	
--	------------	--

	PRELOAD /mm	
--	-------------	--

0	REBOUND %	0
---	-----------	---

☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO
☐ YES ☐ NO	O-RING ON SHAFT	☐ YES ☐ NO

☒ 3 HOLES	PISTONS	☐ 3 HOLES
☐ 4 HOLES	1.0mm	☒ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TIRES	
INSERTS	
ETS	ETS
5min	10min

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

WHEELS	
S ☐ M ☐ H ☐	HARDNESS
S ☐ M ☐ H ☐	

MOTOR	4.5T	TIMING
ROTOR		ARMATURE

ESC	BATTERIES
-----	-----------

BODY	Nazda2.0	WING	MR33
------	----------	------	------

● ☒ - APPLIED S - SOFT M - MEDIUM H - HARD

XRAY T4'14

FRONT	REAR
 CASTER 0° ☐ 2° ☐ 4° ☒ 6° ☐ SHIM 1 /mm WHEELBASE/mm 256 RIDE HEIGHT/mm 5.5	 RIDE HEIGHT/mm 5.5

C-HUB	SHIM 1.5 /mm	LONG 52mm ☐ SHORT 50mm ☒	SHIM 1.5 /mm	SHIM 1 /mm	LONG 52mm ☒ SHORT 50mm ☐	SHIM 3.5 /mm	REAR HUB
M ☐							M ☐
H ☒							H ☒
ALU ☐							ALU ☐
STEERING BLOCK							
M ☒							
H ☐							
ALU ☐							
OFFSET							OFFSET
STANDARD ☒							STANDARD ☒
	6	DOWNSTOP /mm	5				

FF	FR	RR	RF
ROLL CENTER	ECCENTRIC BUSHINGS		

TOE /deg.	FINAL TOE IN	OUTBOARD TOE
TOE OUT 2		
SHIM UNDER SHOCK	ACKERMANN SHIM	SHIM UNDER SHOCK
SHIM /mm	SHIM /mm	SHIM /mm
STEERING ARM	STANDARD ☐	ALU ☒
ROLL CENTER UPPER CLAMP		ROLL CENTER UPPER CLAMP

FRONT	REAR	
1.5	CAMBER /deg.	2
UPPER SHOCK POSITION		
FRONT ARM	REAR ARM	
STANDARD (H) ☐	STANDARD (H) ☐	
GRAPHITE (G) ☒	GRAPHITE (G) ☒	
GRAPHITE PLATE	GRAPHITE PLATE	
YES ☐ NO ☒	YES ☐ NO ☐	

BALANCE /g	TOP DECK	BALANCE /g
	2.0mm ☐	
	1.6mm ☐	
ECCENTER /mm		ECCENTER /mm
STANDARD ☐		STANDARD ☐
1		1
DIFF POSITION		DIFF POSITION
UP ☒		UP ☒
DOWN ☐		DOWN ☐
LOWER SUSP. BLOCK		LOWER SUSP. BLOCK
SOLID 1pcs ☒		SOLID 1pcs ☒
SINGLE 2 pcs ☐		SINGLE 2 pcs ☐

COMMENTS