

SET-UP SHEET

XRAY T4'14

RACE	ICC- essex winter series		
TRACK	ews		
NAME	Anonymous		
CITY / COUNTRY	essex	UK	
CONTACT	ollyrcracer@yahoo.com		

DATE	22/02/2014	TEMPERATURE / °F or °C	AIR	20	TRACK
------	------------	------------------------	-----	----	-------

QUALIFYING POSITION	4	BEST LAPTIME /sec	12.45	FINAL POSITION	5	RACE LENGTH /minutes	5
---------------------	---	-------------------	-------	----------------	---	----------------------	---

TRACK CONDITION	☒ CARPET	☐ ASPHALT	
	☐ TECHNICAL	☒ FAST	
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH

FRONT	REAR
TRANSMISSION	

SOLID AXLE	☒ YES	BALL DIFFERENTIAL	☐ YES
SOLID ONE WAY DIFF.	☐ YES		
ONE WAY DIFFERENTIAL	☐ YES		

GEAR DIFFERENTIAL	☐ YES	GEAR DIFFERENTIAL	☒ YES
OIL		OIL	4k /Cst

PINION / T	21	SPUR GEAR / T	84
FINAL DRIVE RATIO	4	ROLLOUT	NaN

FRONT	REAR
-------	------

2.5-2.8	XRAY SPRINGS	2.5.
---------	--------------	------

350	OIL / CST	350
-----	-----------	-----

	LENGTH /mm	
--	------------	--

	PRELOAD /mm	
--	-------------	--

0	REBOUND %	0
---	-----------	---

☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO
☐ YES ☒ NO	O-RING ON SHAFT	☐ YES ☒ NO

☐ 3 HOLES	PISTONS	☐ 3 HOLES
☒ 4 HOLES	1.0mm	☒ 4 HOLES
	1.1mm	
	1.2mm	
	OTHERS	

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

ride rex 30	TIRES	re rex 30
-------------	-------	-----------

	INSERTS	
--	---------	--

	ADDITIVE	
--	----------	--

	ADDITIVE TIMING	
--	-----------------	--

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

ride	WHEELS	ride
------	--------	------

S ☐ M ☐ H ☒	HARDNESS	S ☐ M ☐ H ☒
---	----------	---

MOTOR	reedy 4.5	TIMING	18
-------	-----------	--------	----

ROTOR	std	ARMATURE	
-------	-----	----------	--

ESC	lrp flow	BATTERIES	reedy
-----	----------	-----------	-------

BODY	pf speed 6 light	WING	std
------	------------------	------	-----

☒ - APPLIED	S - SOFT	M - MEDIUM	H - HARD
---	----------	------------	----------

FRONT	REAR
CASTER 0° ☐ 2° ☐ 4° ☒ 6° ☐ SHIM 1 /mm WHEELBASE/mm 257 RIDE HEIGHT/mm 5.75	RIDE HEIGHT/mm 5.75

C-HUB M ☒ H ☐ ALU ☐ STEERING BLOCK M ☒ H ☐ ALU ☐ OFFSET STANDARD ☒	SHIM 2 /mm LONG 52mm ☒ SHORT 50mm ☐ SHIM 2 /mm LONG 52mm ☐ SHORT 50mm ☒ SHIM 1 /mm LONG 52mm ☐ SHORT 50mm ☒ SHIM 4 /mm LONG 52mm ☒ SHORT 50mm ☐ REAR HUB M ☐ H ☒ ALU ☐ OPTIONAL HUB MEASURE UNDER ARM 5.5 DOWNSTOP /mm 4.5	REAR HUB M ☐ H ☒ ALU ☐ OPTIONAL HUB MEASURE UNDER ARM 4.5
--	--	---

FF ☐ 0.5 ☒ FR ☐ 0.5 ☒ RR ☐ 0.5 ☒ RF ☐ 0.5 ☒ ROLL CENTER ECCENTRIC BUSHINGS

TOE /deg. FINAL TOE IN 2.5 OUTBOARD TOE TOE OUT 0.5 SHIM UNDER SHOCK 2 /mm ACKERMANN SHIM 0 /mm STEERING ARM STANDARD ☐ ALU ☒ ROLL CENTER UPPER CLAMP	SHIM UNDER SHOCK 2 /mm ANTI ROLL BAR ROLL CENTER UPPER CLAMP
---	---

FRONT	REAR
1.75 CAMBER /deg. 2 UPPER SHOCK POSITION FRONT ARM STANDARD (H) ☐ GRAPHITE (G) ☒ GRAPHITE PLATE YES ☐ NO ☒	REAR ARM STANDARD (H) ☐ GRAPHITE (G) ☒ GRAPHITE PLATE YES ☐ NO ☒

BALANCE /g 10 TOP DECK 2.0mm ☒ 1.6mm ☐ ECCENTER /mm STANDARD ☒ DIFF POSITION UP ☒ DOWN ☐ LOWER SUSP. BLOCK SOLID 1pcs ☒ SINGLE 2 pcs ☐ BALANCE /g 15 BALANCE /g 10 ALU STAND YES ☒ NO ☐ BALANCE /g fan	BALANCE /g 10 TOP DECK 2.0mm ☒ 1.6mm ☐ ECCENTER /mm STANDARD ☒ DIFF POSITION UP ☒ DOWN ☐ LOWER SUSP. BLOCK SOLID 1pcs ☐ SINGLE 2 pcs ☒ BALANCE /g 15 BALANCE /g 10 ALU STAND YES ☒ NO ☐ BALANCE /g fan
---	---

COMMENTS
Ecs rear driveshafts Hudy servo horn