



SETUP SHEET

Driver:

| Track/Event: | | | | | | Date: | | | | |
|--------------|----------------------------------|-------------------|-----------------------------------|--------------------|----------------------------------|--|------------------------------------|---------------|---------|---------------|
| C | ar: | | ESC Firmware: | | | | Traction: □ Low | | | |
| N | lotor: | | Battery: | | | | Medium High | | | |
| R | otor: | | Comments/Results: | | | | | | | |
| Timing: | | Gear | Gearing: | | | | | | | |
| S | ettings | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 1 | Running Mode | Forward, Brake | Forward, Reverse with Brake | Foward, Reverse | Zero Timing Forward, Brake | Zero Timing Forward, Reverse with Brake | Zero Timing Forward, Reverse | | | |
| 2 | Drag Brake Force | 0% | 5% | 10% | 15% | 20% | 25% | 30% | 100% | User Setting: |
| 3 | Low Voltage Cut-Off Threshold | No Protection | 2.6V/CeII | 2.8V/Cell | 3.0V/Cell | 3.2V/Cell | 3.4V/Cell | User Setting: | | |
| 4 | Start Mode(Punch) | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 | Level 6 | Level 7 | Level 8 | Level 9 |
| 5 | Max Brake Force | 12.50% | 25% | 37.50% | 50% | 62.50% | 75% | 87.50% | 100% | |
| 6 | Max Reverse Force | 25% | 50% | 75% | 100% | | | | | |
| 7 | Initial Brake Force | Drag Brake | 0% | 20% | 40% | | | | | |
| 8 | Neutral Range | 6% (Narrow) | 9% (Normal) | 12% (Wide) | | | | | | |
| 9 | Over-heat Protection | Enable | Disable | | | | | | | |
| 10 | BoostTiming | 0° | User Setting: | | | | (0°-16° 1° steps) | | | |
| 11 | Boost Start | 5000 RPM | User Setting: | | | | (1000-15000 RPM 50RPM steps) | | | |
| 12 | BoostTiming Acceleration | For stock only | User Setting: | | | | (50-750RPM/def 50RPM steps) | | | |
| 13 | Turbo Timing | 10° | User Setting: | | | | (0°-20° 1° steps) | | | |
| 14 | Turbo Slope Rate | 3°/0.1s | 6°/0.1s | 12°/0.1s | 18°/0.1s | 24°/0.1s | Fastest | | | |
| 15 | Turbo Delay | Os/off | 0.1s | 0.2s | 0.3s | 0.4s | 0.5s | 0.6s | 0.7s | 0.8s |