AC 10		roc Champlin	LEVGILB	JConcepts Midwest Carpet Nationals	<u> </u>
	Dalesocto	ober 27, 2019	_ Treels	Thunder Road R/C Raceway	
TEAM KIT	Qualify8 2nd	_tiQe □ Meffi	श्रीरीतीरी र	Best Lap Tilmes_	
Front Suspension:				Res	et Forms
Ride Height: 14 mm	Anti Roll Bar:	<b>Bump Steer Spa</b>	cing: 0 mm AxI	le Height: Ball Stud Spacing	0 mm
Camber: -3*	White (0.8mm)	] \	+3	<u> </u>	
<b>70e:</b> 0 (Tierod Gap = 27.5 mm)	Gray (0.9mm)	<u> </u>	+2		<b>EO</b>
Arm Type: #91674 Gullwing, Hard		╣ \	/ +1 0	님	
Tower Type: #91768 Gullwing		<u> </u>	5,000		
Caster Block Insert: 2.5*	Ť			•	300
Steering Block: 3	Steering Plate: #916				2 1
Bulkhead Type: #91659 Brass	Steering Stop Spaci	ng: 0 mm	Ball Si	tud Spacing: 1 mm	
Kick-Up Angle: 25*	╡ \ ██		_ BA		06
Wheel Hex: #91682 Aluminum	╡ \■				
Notes: #1366 FT Aluminum Servo Horn, 25T	$\exists$		. 45	3	2 1
#91669 FT Aluminum Steering Rack					
#91668 FT Aluminum Steering Bellcranks			7		
				000	
	Caster Block Spacin	<b>1</b> mm		CBA	
Rear Suspension:					
Ride Height: 14 mm	Anti Roll Bar:	Rear Hub Link S		UIC. IC.	
Camber: -3*	White (1.2mm) Gray (1.3mm)	]   Plastic Hub 🔲	Aluminum Hub 🔲 🛚 B	all Stud Spacing: 3 mm 327	
Tower Type: #91769 Standard	Blue (1.4mm)	BOA	0 8		H
Wheel Hex: #91610 FT Clamping Wheel Hex, 7.0 m			Down E C A	OB E	
CVA Bone Length: #91434 67 mm	<u> </u>				1-1
CVA Pin Location: Towards Hex	C Mount Inserts: 1°	0 .5° 🔲			
Hub Spacing:	Aluminum 🔳 Brass				3 2 1
Forward Middle Back				M	000
Shock Mounting Position:	000			.//!!!!	Z <del>u</del>
Front of Arm Rear of Arm	D Mount Inserts: 1° Aluminum Brass			(0)	
Notes: #91778 B6.1 Rear Arms, Hard (Shimmed Back 2 mr			Insert:	DCBA	
		Hub +3	<b>1</b> +2 □ +1 □ 0 □	Ball Stud Spacing: 3 mm	
Electronics:	Drivetral		Shocks:		
Radio: Sanwa M12S Servo: #27100	0 Reedy RS1206 <b>Transmissi</b>	ion: Laydown:	¬I =	Front Rear	1
EPA: Throttle: 100 % Brake:	100 <b>%</b> 3 Gear:	Layback:	511 <u> </u>	91625 2x1.5 Flat Machined #91626 2x1.6 Flat Machined	
ESC: #27004 Reedy Blackbox 510R	4 Gear:	Stand Up:	Fluid:	#5429 FT 35 wt #5422 FT 30 wt	
ESC Settings: See Setup Sheet	Differentie	al: Ball Diff:	Spring:	#91834 Yellow V2 #91840 Blue V2	
Motor: Reedy M3 (#276 13.0mm Mod R	Rotor) Height:2	Gear Diff:	Limiters:	0 In / 1 Out 0	
Wind: 6.5 Timing:	22* Notes:	20,000 - 4 Gear	Stroke:	23.5 mm 27.5 mm	Stroke
Pinion: 21 Spur:	78 Slipper G	luich:	Eyelet Length:	Short Long	]
<b>Baffery:</b> #27338 Reedy Zappers SG2 4100 mAh 80C + #91744 F	Type:	Team Associated	Cup Offset:	5 mm 0 mm	
Battery Position: 5F	# of Pads:	2 x White	Notes:	#91494 Machined Shock Spacers V2 / X-Rings	
Track Info:		Tires:		Body, Wing, Weight:	}
Size: Small Medium Lo	arge 🔲 Extra Large 🔲	Front Tires:	JConcepts Swaggers (Spec)	<b>Body:</b> JConcepts Finnisher	Lightweight
Surface: Dirt Carpet As	stroturf Multi Surface	Front Compound	Double Pink	Wing: JC Lower Front Wing / JC	
	igh 🔲 Very High 🔳	Front Insert:	None	Wing Angle: 0° 3°	□ 6° ■
	/et	Rear Tires:	JConcepts Twin Pin (Spec)		hind Servo
	usty Hard Packed		<b>D</b> ouble Pink	None Aluminum Steel	Other 🗌
	mooth Loamy	Rear Insert:	JConcepts Open Cell	Electronic Weights:	
Temperature: Ambient: 60F Track: 60F		Wheel (F/R):	Team Associated Hex	None Aluminum Steel	
Notes: CRC Black Carpet Notes: Total Vehicle Weight: 1520g					
Vehicle Gomments:  Notes: #91755 Ti Screw Kit (only used above chassis): #91576 & 91577 Fox Shock Bodies; #91616 & 91620 FT Chrome Shock Shafts; #91796 FT Motor Plate, Graphite					
Notes: #91/55 Ti Screw Kit (only used above chass	رهار; #91576 & 91577 Fox Shock Bodie	s; #91616 & 91620 FT Chrome	Snock Shafts; #91796 FT Motor	Plate, Graphite	