RCIO	Differs	Ryan Cavalieri 2017 F				Reedy International Off-Road Race of Champions	
	Delles January 21, 2017 Tracks		00	OCRC Raceway			
TEAM KIT	Quellity8 N/A		Mellos N/A Gill	n1s1/18 1 Bes	emiir qwl 1	19.8	
Front Suspension:	22-					et Forms	
Ride Height: 22 mm	Anti Roll Bar:	Bump Steel	r Spacing: 1 mm	Axle Height:	Ball Stud Spacing:	9 mm	
Camber: -1*	None	<u> </u>		+3			
Toe: +1*	White (0.8mm)	╣ \		→ +2 -1 □	\		
Arm Type: #91673 Gullwing, Hard	Gray (0.9mm) [╣ \	am	$\left/\right _{0}^{+1}$			
Tower Type: #91663 Gullwing	Other:	i	5.00				
Caster Block Insert: 5*	<u> </u>				3		
Bulkhead Type: #91656 Plastic	Steering Plate:	#91680 +1	6		2	7	
Kick-Up Angle: 25*	Steering Stop Space	ing: 0	B	Ball Stud Spacing:	1 mm		
Wheel Hex: #91682 Aluminum			_	an elea opaamy			
Notes: #91667 Plastic Steering Rack & Bellcranks				BA			
#1366 FT Aluminum Servo Horn, 25T					3 2	O	
0.5 mm Shim Between Bulkhead & Chassis						0	
					N		
	Caster Block Spacis	ng: 1 mm		C B			
Rear Suspensions							
Ride Height: 22 mm	Anti Roll Bar:	R	Rear Hub Link Settii	ng:			
Camber: -1*	None		E C A		3		
Wheel Hex: #91609 6.0 mm	White (1.2mm)	-	Up D B		21		
Hub Spacing:	Gray (1.3mm) [Blue (1.4mm) [╣					
Forward Middle Back	Other: [╣	Down D B C A	Ball Stud	Spacing: 0.5 mm	6	
Shock Mounting Position:							
Front of Arm 🔳 Rear of Arm 🗌	C Mount Inserts: 1	° 🔳 0 .5° 🔲				321	
Nofes: #91690 Brass "C" Arm Mount, 25G	Ī 					·000	
#91688 Aluminum "D" Arm Mount	_				45mm		
#91696 Rear Arms, Hard	D Mount Inserts: 1	°□ 0.5°□				(0)	
B6 Prototype Hubs / Back Row Inside + 4mm; 67 mm CVA		888	Hub Insert:	BA			
			+3 -+2 -+1	0			
Electronics:	Drivetra		Shocker				
Radio: Sanwa M12S Servo: Savox			_	Front	Rear		
EPA: Throttle: 100 % Brake:	88% % 3 Gear: Stand Up:	4 Gears:: Lay Do:		2 x 1.6 Flat	2 x 1.7 Flat		
ESC: Muchmore Felta Pro V2				32.5 wt	30 wt		
ESC Settings: N/A	Differenti		Spring:	Gray	Green		
Motor: Muchmore Felta XZ (Reedy #271 12.0mm		Gear D		1	0		
Wind: 7.5 Timing:	16* Notes:		Stroke:	20.9 mm	28.6 mm	Stroke	
Pinion: #1339 Factory Team 21T Spur:	78 Slipper (Eyelet Leng		Long		
Battery: Muchmore Impact 5000 mAh (#MLI-S		7495 Vented Team Assoc			5 mm		
Battery Position: 4F	# of Paas	#91197 LCF Slipper	Pads (2) Notes:		ternals, #91493 X-Rings		
Track Info					Ving, Weights		
	arge Extra Large	51=			JConcepts S2 Light		
	stroturf Multi Surface	Front Comp			JC Aero Long Cord / JC Nar		
	igh 🔳 Very High 📙	Front Inser			gle: 0°	6° <u>■</u>	
	/et	Rear Tires:					
	usty Hard Packed				Aluminum Steel	Other 🗌	
	mooth Loamy	Rear Insert			ic Weights:		
Temperature: Ambient: 50F	Track: 50F	Wheel (F/R	•		Aluminum Steel	Other 🗌	
Notes: Raining Ou	ıtside	Notes:	Reedy Race Spec Additive	Total Vel	hicle Weight:		
Vehicle Comments:							
Notes: #91755 Ti Screw Kit (only used above chassis); #91653 Side Rails, Hard; #91696 & 91620 Chrome Shock Shafts; #91576 & 91577 Kashima Shock Bodies; JConcepts Carbon Fiber Battery Strap & Spur Gear Guard							