

SET-UP SHEET

AIR TEMP F° C°

LAPS

BEST LAP TIME in LAP

TRACK SIZE
☐ OPEN ☐ MEDIUM ☐ TIGHT

TRACK TRACTION
☐ HIGH ☐ MEDIUM ☐ LOW

DIFFERENTIAL OIL

FRONT	CENTER	REAR
STD	STD	STD

OIL wt.

FRONT	CENTER	REAR

GEARING

SPUR GEAR	T
PINION GEAR	T

TIRES

FRONT TYPE

COMPOUND

INSERT FOAM

REAR TYPE

COMPOUND

INSERT FOAM

ELECTRIC MOTOR

TURN /

RPM

KV

BRAND

ELECTRIC SPEED CONTROLLER

BRAND

TYPE

NAME RACE DATE

TRACK CITY/COUNTRY TRACK CONDITION

FRONT

STEERING BAR
☐ A ☐ B ☐ C

STEERING KNUCKLE ARM
☐ PLASTIC
☐ ALUM

FRONT SPINDLE CARRIERS
☐ PLASTIC
☐ ALUM

FRONT SPINDLE CARRIERS CASTER
☐ 20°
☐ 22°
☐ 24°

INSERT NR.

TOTAL CASTER
☐ 18° ☐ 22.5°
☐ 18.5° ☐ 23°
☐ 19° ☐ 23.5°
☐ 19.5° ☐ 24°
☐ 20° ☐ 24.5°
☐ 20.5° ☐ 25°
☐ 21° ☐ 25.5°
☐ 21.5° ☐ 26°
☐ 22°

SHOCK
 SHOCK LENGTH mm
 OIL wt.
 PISTON
 SPRING

SHOCK LENGTH

REAR

WHEEL HUB
☐ 0
☐ +1.9mm

REAR HUB
☐ PLASTIC
☐ ALUM

SHOCK
 SHOCK LENGTH mm
 OIL wt.
 PISTON
 SPRING

SHOCK LENGTH

WHEELBASE SHIMS
☐ 0mm ☐ 2mm
☐ 2.5mm ☐ 4.5mm

INSERT NR.