



SETUP SHEET

Driver Date Track Event **Track Condition** Temperature Ride Height Front Shocks **Front** Front Shock Towe В mm Camber Angle Oil weight 00 wt Toe Angle 0 Piston 3 cxxx 3 Sway Bar mm 2 2 mm CVA Bladder 1 Droop Universal mm Std Spring Narrow Shock Length Narrow+Heavy mm 99 0° 2 2° ___ 2° ___ 4° Notes 15° 17.5° Caster Angle 2 3 4 5 A-Mount Pills 2 20° Wing Body Ride Height Rear Shocks mm Rear Camber Angle Oil weight High Low 1 2 3 wt Toe Angle Piston 3 АВС Sway Bar 2 mm _ 1 mm Bladder Droop CVA 3 Universal Spring Shock Length Std Narrow Narrow + Heavy O 3.00 (i) 00 Notes Rear Hub Outboard Toe 0° Wide 1.0 2.0 2.75 3.0 3.25 3.5 D-Mount 0° Narrow 0.5° In 2 3 4 5 D-Mount Pills 0.5° out 3 4 C-Mount Pills C-Mount **Engine Tires** Front Rear Front Arms Rear Arms Brand mm Spur gear Clutch Bell mm Compound Clutch Shoes Insert Clutch Springs Wheel Glow Plug Notes Glow Fuel Diff Oils Front Center Rear Notes Brand Oil Weight / Grade Download the newest Set-Up sheets on our website: www.HBRACING.com