

SETUP SHEET

Qual. / Finish: A8 / A9

Surface: ☒ Smooth ☐ Med. ☐ Rough

Traction: ☒ High ☐ Med. ☐ Low

☐ Wet ☒ Dry ☐ Sandy ☐ Clay

☐ Soft Dirt ☐ Grass ☐ Dusty ☐ Blue Groove

☒ Other ☐ Indoor ☐ Outdoor

Center Drive: ONE-WAY

Technical drawing of a cable clamp assembly. The assembly consists of a top mounting bracket, a central cylindrical body, and a bottom hook. A dimension line on the left indicates a length of 100 mm for the central body.

Technical drawing of a mechanical assembly, likely a robotic arm or gripper, showing various adjustment points. The drawing includes labels for angles and distances:

- Top right: Four adjustment points labeled 1, 2, 3, and 4. Point 2 is marked with an 'X' symbol.
- Center: A distance of -1 mm is indicated for a horizontal adjustment.
- Right side: A distance of 1 mm is indicated for a horizontal adjustment.
- Bottom left: Three angle settings are shown: 2.0°, 2.5°, and 3.0°. The 3.0° setting is marked with an 'X' symbol.
- Bottom right: Two adjustment points labeled 1 and 2. Point 1 is marked with an 'X' symbol.
- Legend on the right:
 - X 0°
 - 0.5°
 - 1.0°

Sway Bar: Non

Memo:	Losi Red Spring AE Oil
--------------	---------------------------

Body:	Cyclone D4 Body
Wing:	175 Curved - Half Flap

Wheel:	HB
---------------	----

Send Mail

