

Name _____ Date _____ Track / City _____ Event _____

Front Suspension:

Shock Stay:
☐ UM511(RB5)
☐ UM525(WC Edition)

Upper Spacer: _____ mm

4.8mm Ball Stud:
☐ UM128(WC Edition)
☐ UMW508 (+2mm High Mount)

Camber: _____ °
 - +

Ackerman Steer Spacer: _____ mm

4.8mm Ball Stud:
☐ LA246(WC Edition)
☐ UM129(Std)

Shock Stay:
☐ UM511(RB5)
☐ UM525(WC Edition)

Toe: ☐ In ☐ Out _____ °

Front Bulkhead Weight Placement:
☐ None
☐ Bulkhead Inside _____ oz _____ g
☐ On the skid plate _____ oz _____ g * 1oz=28g

Caster:
☐ 25°
☐ 30°

Spacer:
☐ 0.5
☐ 1.0
☐ None

Axle Type:
☐ UM506(Std/Steel)
☐ UM569(WC Edition)

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Axle Height Spacer:
☐ Up
☐ Down

Wheelbase: ☐ Long ☐ Middle ☐ Short

Comments: _____

Rear Suspension:

Shock Position:

Wing Stay Position:

Upper Arm Position:
4.8mm Ball Stud:
☐ 97050M(Std)
☐ UM129

Upper Spacer: _____ mm

Sus. Arm:
☐ LA272(Std)
☐ UM713

Camber: _____ °
 - +

Hub Carrier:
☐ Type-B (UM519)
☐ Type-B2 (UM519-2)

Upper Spacer: _____ mm

Shock Position:

Wheelbase:
 Front: _____ mm
 Rear: _____ mm

Slipper Type:
☐ Separates ☐ Direct

☐ 0°Type-B(UM519)
☐ 0°Type-B2(UM519-2)
☐ 0°Alu(UMW704-0)
☐ 0.5°Alu(UMW704-05)
☐ 1°Alu(UMW704-1)

Sway Bar:
☐ None
☐ _____ mm

Lower Sus Holder Block:
 Front _____ Rear _____

Lower Sus Holder Spacer:
 Front _____ mm Rear _____ mm

Comments: _____

Shock:

Shock Piston: _____

Shock Oil: # _____

Shock Spring: _____

Limiters:
 in out mm in out mm

Shock Length(A): _____ mm

Shock Top Type: ☐ Alu(UM719/Std) ☐ UM753-1

5.8mm Ball End:
 Front: ☐ S ☐ M ☐ L
 Rear: ☐ S ☐ M ☐ L

Chassis:

Ride Height:

Front: _____ mm

Rear: ☐ A ☐ B _____ mm

Tire: Front _____ Rear _____

Compound: _____

Inserts: _____

Wheel: _____

Notes: _____

Comment :

Electronics:

Battery: ☐ Saddle ☐ Short

Motor Position: ☐ Front ☐ Rear

Servo Mounting: ☐ Straight ☐ Sideways

Motor: _____

Motor Timing: _____

Pinion/Spur: _____

ESC: _____

Setting: _____

Radio: _____

Servo: _____

Body / Wing:

Body: _____

Wing Mount: ☐ Narrow ☐ Wide

Wing Dum Height: _____ mm

Wing: _____

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

Lip Height: _____ mm

Material:

Screw: ☐ Steel ☐ Titanium

Pinion Gear: ☐ Steel ☐ Aluminium

Shock O-Ring: ☐ O-ring ☐ X-ring ☐ Red ☐ Clear

☐ Smooth ☐ Sandy
☐ Bumpy ☐ Soft Dirt
☐ Low Traction ☐ Grass
☐ Med.Traction ☐ BlueGroove
☐ High Traction ☐ Clay
☐ Wet ☐ Dusty
☐ Dry ☐ _____