

Rudebits DB2 Setup Sheet

KYOSHO

Name _____ Date _____ Track _____ Event _____

Front Suspension



Upper Spacer: _____ mm

4.8mm Ball Stud: ☐ UM128 (Std) ☐ UMW508 (+2mm High Mount)


4.8mm Ball Stud Spacer: _____ mm

Toe: ☐ In ☐ Out _____°

Tie Rod: _____

Front Bulkhead Weight Placement: ☐ None ☐ Bulkhead Inside _____ oz _____ g ☐ On the skid plate _____ oz _____ g

*1oz=28g

Caster:  ☐ 25° ☐ 30° ☐ 0.5 ☐ 1.0 ☐ None

Spacer: ☐ A (UM502) ☐ B (UM721/Std) ☐ C (UM567)

Caster Block: ☐ 0° ☐ 2° ☐ 4° ☐ IN (wide/Std) ☐ OUT (Narrow)

Front Axle: ☐ UM569 (RB6) ☐ UM506 (RB5)

Comments: _____

4.8mm Ball Stud: ☐ LA246 (-1mm Low Mount) ☐ 97050M (Std)

Ackerman Steer Spacer: _____ mm

Wheel Hub: _____ mm

Wheelbase: F: _____ mm R: _____ mm


Wheel Spacing: ☐ Out _____ mm ☐ In _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer: ☐ _____ mm ☐ _____ mm

Caster Block position: _____

Rear Suspension



Wing Height: _____

Shock Stay: ☐ LA217(SP) ☐ LA217H

Spacer: _____ mm

Camber Angle: _____°

Sway Bar: _____

Sus. Holder(RF): ☐ IN ☐ OUT _____

Sus. Holder(RR): ☐ IN ☐ OUT _____

Ride Height: _____ mm

Sus. Holder Spacer: Front ☐ ☐ ☐ ☐ ☐ ☐ Rear ☐ ☐ ☐ ☐ ☐ ☐

Shock stay height: _____

Type-B Type-B2

Spacer: _____ mm

Wheel Spacer: _____ mm

Hub Spacer: F: _____ mm R: _____ mm

Rear Sus. Arm: ☐ LA272(UM566,UM521)(SP) ☐ UM521-1(1-Hole) ☐ LA255

Rear Hub add Toe: ☐ 0°Type-B(UM519) ☐ 0°Type-B2(UM516-2) ☐ 0°Alu(UMW516-0) ☐ 0.5°Alu(UMW516-05) ☐ 1°Alu(UMW516-1)

Shock

Front Rear

Shock Piston: _____

Shock Oil: # _____ # _____

Shock Spring: _____

Limiters: in mm out mm in mm out mm

Shock Length(A): _____ mm _____ mm

Shock Top Type:  Std:RB5 Low:ZX5FS  Std:RB5 Low:ZX5FS

5.8mm Ball End: Front:  S ☐  M ☐  L Rear:  S ☐  M ☐  L

Kind in spring

Soft	Pink
	White
	Gold
	Red
	Yellow
	Orange
Hard	Green

Sway Bar

1.0	White
1.1	Pink
1.2	Red
1.3	Orange
1.4	Yellow
1.5	Blue
1.6	Green

Tire

Front Rear

Tire: _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Body/Wing/Other

Body: _____

Wing: _____

Lip height: _____

Wing Angle: 4° ☐ 7° ☐ 10° ☐

Battery Post: ☐ Pla ☐ Alu

Slipper Type: ☐ Direct ☐ Separates

Slipper Sheet(F-R): ☐ Red-White ☐ Red-Red ☐ White-White

Center Post: ☐ Pla ☐ Alu

Back bone screw: ☐ F ☐ R

Comments

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Radio: _____

Servo: _____

Throttle/Brake: _____

EPA: _____ Expo: _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____

☐ Smooth	☐ Sandy
☐ Bumpy	☐ Soft Dirt
☐ Low Traction	☐ Grass
☐ Med. Traction	☐ Wet
☐ High Traction	☐ Dry
☐ Blue Groove	☐ Dusty
☐ Clay	☐ _____