

Rudebits DB2 Setup Sheet

KYOSHO

Name _____ Date _____ Track _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud:
☐ UM128 (Std)
☐ UMW508 (+2mm High Mount)

Camber: _____ °

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Wheel Hub: _____ mm

4.8mm Ball Stud:
☐ LA246 (-1mm Low Mount)
☐ 97050M (Std)

Ackerman Steer Spacer: _____ mm

Bump Steer Spacer: _____ mm

Toe: ☐ In ☐ Out _____ °

Tie Rod: _____

Caster:
☐ 25° ☐ 30° ☐ 0.5 ☐ 1.0 ☐ None

Spacer:
☐ A (UM502)
☐ B (UM721/Std)
☐ C (UM567)

Caster Block:
☐ 0° ☐ 2° ☐ 4°

Caster Block position:
☐ IN (wide/Std)
☐ OUT (Narrow)

Axle Height Spacer:
☐ _____ mm
☐ _____ mm

Front Bulkhead Weight Placement:
☐ None
☐ Bulkhead Inside _____ oz _____ g
☐ On the skid plate _____ oz _____ g

Front Axle: ☐ UM569 (RB6) ☐ UM506 (RB5)

Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Wing Height: _____

Shock Stay:
☐ LA217(SP)
☐ LA217H

Spacer: _____ mm

Shock stay height: _____

Camber Angle: _____ °

Sway Bar: _____

Sus. Holder(RF):
☐ IN ☐ OUT _____

Sus. Holder(RR):
☐ IN ☐ OUT _____

Ride Height: _____ mm

Sus. Holder Spacer:
Front ☐ ☐ ☐ ☐ ☐ ☐ Rear ☐ ☐ ☐ ☐ ☐ ☐

Wheel Spacer: _____ mm

Hub Spacer:
F: _____ mm
R: _____ mm

Rear Sus. Arm:
☐ LA272(UM566,UM521)(SP)
☐ UM521-1(1-Hole)
☐ LA255

Rear Hub add Toe:
☐ 0°Type-B(UM519)
☐ 0°Type-B2(UM516-2)
☐ 0°Alu(UMW516-0)
☐ 0.5°Alu(UMW516-05)
☐ 1°Alu(UMW516-1)

Shock

Front **Rear**

Shock Piston: _____

Shock Oil: # _____ # _____

Shock Spring: _____


Limiters: in out mm mm in out mm mm

Shock Length(A): _____ mm _____ mm

Shock Top Type: ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS

5.8mm Ball End:
Front: ☐ S ☐ M ☐ L
Rear: ☐ S ☐ M ☐ L



Spring

Soft	Pink
	White
	Gold
	Red
	Yellow
	Orange
Hard	Green

Sway Bar

1.0	White
1.1	Pink
1.2	Red
1.3	Orange
1.4	Yellow
1.5	Blue
1.6	Green

Tires

Front **Rear**

Tire: _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Body/Wing/Other

Body: _____

Wing: _____

Lip height: _____

Wing Angle:
4° ☐ 7° ☐ 10° ☐

Battery Post:
☐ Pla ☐ Alu

Slipper Type:
☐ Direct
☐ Separates

Slipper Sheet(F-R):
☐ Red-White
☐ Red-Red
☐ White-White

Center Post:
☐ Pla ☐ Alu

Back bone screw:
☐ F ☐ R

Comments

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Radio: _____

Servo: _____

Throttle/Brake: _____

EPA: _____ **Expo:** _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____

☐ Smooth	☐ Sandy
☐ Bumpy	☐ Soft Dirt
☐ Low Traction	☐ Grass
☐ Med. Traction	☐ Wet
☐ High Traction	☐ Dry
☐ Blue Groove	☐ Dusty
☐ Clay	☐ _____