

InfernoMP10E SETUP SHEET

ver.1.00



Driver		Date	Track	Event	Spur Gear	Pinion Gear
Reno Savoya		08/03/2025	The Dirt Perris Condition : 15°C	DNC 2025	☐ 46T(Std.) ☐ 47T ☐ 48T	20 T
Motor	Battery	ESC	Tires	Tire Insert	Wheel	Body
Konect 2050kv G2	8200 Gens Ace	Konect RS8 ELITE	Matrix Neutron Compound : US	Matrix	Matrix	TKI2

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ Std. ☐ LSD IFW621	☒ Std. ☐ LSD IFW622	☒ Std. ☐ LSD IFW621
Ring Gear	☒ 43/13 ☐ 42/12	15 000 # 7 000	☒ 43/13 ☐ 42/12
			3 000 #

● Shock Set-Up

	Front	Rear
Shock Type	P: w/Diaphragm A: Aeration 50 - A	58 - A
Shock Piston	B: Black W: White T: Taper W: 5x1,4 B: 5x1,5	
Shock Oil	# 500	# 400
Shock Spring	Length 70mm Color red	Length 81mm Color red

● Ride Height

Front	Rear
26 mm	29 mm

● Rebound

Front	Rear
107 mm	124 mm

● Camber Angle

Front	Rear
+ -2°	+ -3°


● Toe Angle

Front	Rear
+ -2°	☐ 2.5° ☒ 3° ☐ 3.5°

● Wheelbase

Collar of Rear Hub	Front Side	Rear Side
	5 mm	0 mm

● Shock Mount Position



Shock Stay

Front	Std.	Long
	☐	☒
Rear	Std.	Long
	☐	☒


Rear Upper Shock Bush

Std.	Long
☒	☒

Sus. Arm

Front	In	Out
	☐	☒
Rear	In	Out
	☐	☒

● Rear Upper Arm Position



Plastic	Aluminum
☐	☒

Hub Carrier Bush	Plastic	Brass
	☒	☐

● Rear Wheel Hub

Narrow	Std.	Wide
☒	☐	☐


● Front Sus. Arm

Soft (Std.)	Hard
☒	☐

● Front Sus. Bush

Rear Side	[x] [x]
-----------	---------

● Front Upper Arm Position




● Front Wheel Hub

Narrow	Std.	Wide
☐	☒	☐

● Front Hub Carrier

☐ Plastic	☒ Aluminum		
☐ 13°	☐ 16°	☐ 17.5°	☐ 19°



● Rear Sus. Bush

Front Side	[x] [x] [x] [x]
Rear Side	[x] [x] [x] [x] [x] [x] [x] [x]


● Rear Sus. Arm

Soft (Std.)	Hard
☐	☒
Rear Sus. Bush	
Short	[x]
Medium	[x]
Long	☒

● Servo Horn

Steering	Throttle
☐ Plastic	☐ Plastic
☐ Alum. Long	☐ Aluminium
☒ Alum. Short	

● Steering Plate



● Sway Bar

Front	Rear
$\varnothing$ 2,3mm	$\varnothing$ 2,7mm
0 mm	2 mm

● Weight

Front	Rear
☒ None	☐ None
☐ IFW604-10	☐ IFW605-10
☐ IFW604-20	☒ IFW605-20
☐ other	☐ other

● Wing

IF491(TKI4)	Flap	None
☒	☐	☐
	☐ 5mm	☐
	☐ 8mm	☐
	☒ Holes	

**0.8 module with 59T spur gear
IFW643 steering with KPI. C-hub all the way
back, knuckles down, 18° caster, link to the inside**

Am0 - Peltric.com

Notes