

Driver		Date	Track / Event		Engine	Plug	Manifold	Muffler
John Doe			Starting setup 0 option					
Spur Gear	Clutch Bell	Clutch Spring	Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
☒ 0.8 ☐ 1.0 59 T	☒ 0.8 ☐ 1.0 16 T	☒ 0.90 ☐ 1.00 ☐ 0.95 ☐ 1.10	Carbon X AL. IFW636 X3	Tire : Compounds:			Mp11	

Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12 Diff. Size ☒ Small ☐ Large	☒ 10/20 ☐ 12/18 ☐ LSD Diff. Size ☒ Small ☐ Large	☒ 10/20 ☐ 12/18 ☐ LSD Ring Gear ☒ 43/13 ☐ 42/12 Diff. Position ☐ Low ☐ Mid. ☒ High
	10k	10k	5k

Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration Size 50 A Type	Size 58 A Type
Shock Piston	B : Black W : White T : Taper 5x1,4mm	5x1,5mm
Shock Oil	450	550
Shock Spring	Stock	stock
Shock Length (Ball to Ball)	107 mm	120 mm

Front

☐ Suspension Holder Bushing

☐ Wheel Nut

☐ Wheel Hub
☐ Narrow
☒ Std.
☐ Wide

☐ Camber
 -2 deg.

☐ Spacer

☐ Hub Carrier Washer

☐ Steering Plate

☐ Servo Saver Bushing

☐ Tie Rod

☐ Universal Swing Shaft
☒ Std. (Cap Type)
☐ IFW703

☐ Suspension Arm Plate
☒ None ☐ Upper ☐ Lower

☐ Servo Horn
☐ AL. 18.5mm ☐ Plastic
☒ AL. 20.5mm

☐ Sway Bar
 2,3 mm

Rear

☐ Suspension Holder Bushing

☐ Wheel Nut

☐ Wheel Hub
☐ Narrow
☒ Std.
☐ Wide

☐ Camber
 -3 deg.

☐ Wheelbase

☐ Torque Rod Plate
☒ Plastic
☐ Carbon
☐ None

☐ Torque Rod Bush
☒ Plastic
☐ Rubber

☐ Servo Horn
☒ Plastic
☐ AL.

☐ Universal Swing Shaft
☒ Std. (Cap Type)
☐ IFW703

☐ Suspension Arm Plate
☒ None ☐ Upper ☐ Lower

☐ Sway Bar
 2,8 mm

Other

☐ Chassis Height

 Front 24 mm Rear 28 mm

☐ Chassis Weight

☐ Battery Position

☐ Wing
☒ Plastic ☐ PC
 13 mm
 Wing Position ☒ Front ☐ Rear
 Wing Spacer

Starting basic setup for all conditions, out of the box with no option

