

Name \_\_\_\_\_

Date \_\_\_\_\_

Track / City \_\_\_\_\_

Event \_\_\_\_\_

### Front Suspension

Carber ☐ + ☐ - \_\_\_\_\_ °

Upper Spacer \_\_\_\_\_ mm

Shock Stay  
☐ Std(UM511)  
☐ Carbon(UMW500)

Toe ☐ In ☐ Out \_\_\_\_\_ °

Front Bulkhead Weight Placement  
☐ None  
☐ Bulkhead \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g  
☐ Chassis \_\_\_\_\_ oz \_\_\_\_\_ g

Caster  
☐ 25°  
☐ 30°

Spacer  
☐ 0.5  
☐ 1.0  
☐ None

Axle Type  
☐ Standard(Steel:UM506)  
☐ Option(Aluminum:UM507)

Axle Spacer  
☐ Out (Standard) \_\_\_\_\_ mm  
☐ In \_\_\_\_\_ mm

Ackerman Steering Spacer \_\_\_\_\_ mm

Bump Steer Spacer \_\_\_\_\_ mm

Axle Height Spacer  
☐ Up  
☐ Down

Wheelbase  
☐ Long  
☐ Middle  
☐ Short

Comments: \_\_\_\_\_

### Rear Suspension

Lower Sus Holder  
 Normal  
 Narrow ☐ RF:RB5  
 Wide ☐ RF2:RB5SP  
 Aluminum(Opt)  
☐ UM511+UM512  
☐ UM514+UM515

Sus Holder Spacer  
☐ 0.5  
☐ 1.0  
☐ None

Anti-Squat \_\_\_\_\_ °

Swing Shaft  
☐ 62.5mm:RB5(UM510,UM510-01)  
☐ 65.5mm:RB5SP(UM522,LA232-01)

Upper Spacer \_\_\_\_\_ mm

Wing Height  
☐ 1  
☐ 2  
☐ 3

Shock Stay  
☐ Std:RB5(UM512)  
☐ Short:RB5SP(UM520)

Lower Arm  
☐ Short:RB5(UM503)  
☐ Middle:RB5SP(UM521)

Axle Spacer  
☐ Out \_\_\_\_\_ mm  
☐ In \_\_\_\_\_ mm

Wheelbase  
☐ Long  
☐ Middle  
☐ Short

Rear Hub add Toe  
☐ 0° (Standard)  
☐ 0.5° (LA244-05)

Sway Bar ☐ None

Wheel Shaft Type  
☐ RB5SP(UM522-02)  
☐ RB5(UM510-02)  
☐ Proline Axle(UM502)

Comments: \_\_\_\_\_

### Shock

Shock Piston \_\_\_\_\_

Shock Oil # \_\_\_\_\_

Shock Spring Limiters  
 in out mm in out mm

Shock Length(A) \_\_\_\_\_ mm

Shaft Length(B) \_\_\_\_\_ mm

Shock Top Type ☐ ☐ ☐ ☐ ☐ ☐

Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS

Rear Shock Body  
☐ Short:RB5SP(M5196-01V) 38mm  
☐ STD:RB5(M5187-01V) 42mm

Rear Shock Shaft  
☐ STD:RB5SP(M5193-01) 50mm  
☐ Opt:ZX5(M5183-02) 54mm

### Body / Wing / Chassis

Wing  
☐ Aquarius(LA239)  
☐ Sagittarius(LA240)  
☐ Aries(LA241)  
☐ Blast-L(LA251)  
☐ Step-L(LA247)  
☐ Step-S(LA247)  
☐ Blast-S(LA247)  
☐ Other: \_\_\_\_\_

Body  
☐ Trident:RB5(UMB01)  
☐ Sword:RB5SP(UMB02)  
☐ Other: \_\_\_\_\_

Battery Placement  
☐ Front ☐ Rear

Wing Angle  
 4° ☐ 7° ☐ 10° ☐

Ride Height ☐ A ☐ B ☐ F \_\_\_\_\_ mm ☐ R \_\_\_\_\_ mm

Weight Placement \* 1oz=28g

### Track Condition

- ☐ Smooth  
☐ Bumpy  
☐ Low Traction  
☐ Med Traction  
☐ High Traction  
☐ Wet  
☐ Dry
- ☐ Sandy  
☐ Soft Dirt  
☐ Grass  
☐ Blue Groove  
☐ Clay  
☐ Dusty  
☐ Other

### Spring / Rate

|     |               |
|-----|---------------|
| #55 | Orange        |
| #60 | Orange Yellow |
| #65 | Yellow        |
| #68 | Blue          |
| #70 | Silver        |
| #72 | Cobalt blue   |
| #75 | Light Green   |
| #80 | Green         |

### Tyre

Front

Rear

Tyre \_\_\_\_\_

Inserts \_\_\_\_\_

Wheel \_\_\_\_\_

Tyre Compound \_\_\_\_\_

### Others

Motor \_\_\_\_\_

Pinion / Spur \_\_\_\_\_ / \_\_\_\_\_

Battery \_\_\_\_\_

ESC \_\_\_\_\_

Comment : \_\_\_\_\_