

Name \_\_\_\_\_ Date \_\_\_\_\_ Track / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

**Upper Spacer:** \_\_\_\_\_ mm

**Shock Tower:** \_\_\_\_\_ mm

**Toe:** ☐ In ☐ Out \_\_\_\_\_°

**Toe Rod:** \_\_\_\_\_ mm

**Front Bulkhead Weight Placement:**

☐ None

☐ Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g

☐ On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g (\*1oz = 28g)

**4.8mm Ball Stud:**

☐ UM128 (Std)

☐ UMW508 (+2mm High Mount)

**Caster:**

☐ 25°

☐ 30°

**Spacer:**

☐ A (UM502)

☐ B (UMW722/Brass)

☐ B (UMW721/Std)

☐ B (UMW723/Alu)

☐ C (UM567)

**Caster Block:**

☐ 0.5

☐ 1.0

☐ None

☐ 0°

☐ 2°

☐ 4°

**Comments:** \_\_\_\_\_

**AI Steering Support:**

☐ None

☐ UMW724

**4.8mm Ball Stud:**

☐ LA246 (-1mm Low Mount)

☐ 97050M (STD)

**Ackermann Steer Spacer:**

\_\_\_\_\_ mm

☐ UMW701 Aluminum ST Plate

☐ UMW702 Aluminum Crank Arm

**Wheel Hub:**

☐ UM569/Std

☐ UM506

**Caster Block Position:**

☐ In (Wide/Std)

☐ Out (Narrow)

**Bump Steer Spacer:**

\_\_\_\_\_ mm

**Axel Height Spacer:**

☐ \_\_\_\_\_ mm

☐ \_\_\_\_\_ mm

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

### Rear Suspension

**Shock Position:**

☐ Front ☐ Rear

**Shock Tower:**

☐ 1

☐ 2

☐ 3

☐ 4

**RR:**

☐ 1

☐ 2

☐ 3

**Mid:**

☐ 1

☐ 2

☐ 3

**Susp Holder Spacer:**

F ☐ 0.5 ☐ 1.0 ☐ None

R ☐ 0.5 ☐ 1.0 ☐ None

**Anti-Squat:** \_\_\_\_\_°

**4.8mm Ball Stud:**

☐ UM129

☐ UMW508 (+2mm High Mount)

☐ 97050M

☐ UM128 (Std)

**Upper Spacer:** \_\_\_\_\_ mm

**Lower Susp Holder:**

Plastic ☐ RF ☐ RF2L ☐ RF2

Option ☐ UMW511GM (RF/Alu)

(Opt/Adjustable)

☐ UMW705 (RF/Alu) \_\_\_\_\_ Block

☐ UMW725 (RF-MID/Bra) \_\_\_\_\_ Block

(Opt/Adjustable)

☐ UMW706 (RR-RWD) \_\_\_\_\_ Block

☐ UMW707 (RR-MID) \_\_\_\_\_ Block

**Universal Swing Shaft:**

☐ 1

☐ 2

☐ 3

☐ 4

☐ 5

**Camber:** \_\_\_\_\_°

**Drive Hub:**

☐ 4mm (TFW113)

☐ 4.5mm (LAW30GM/Std.)

☐ 5.2mm (UMW523)

**Axle Spacer:**

☐ Out \_\_\_\_\_ mm

☐ In \_\_\_\_\_ mm

**Sway Bar:** ☐ None ☐ \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

**Upper Spacer:** \_\_\_\_\_ mm

**Rear Hub Carrier:**

☐ 0° Type-B (UM519)

☐ 0° Type-B2 (UM519-2)

☐ 0° Type-B2 (UM519-2)

☐ 0.5° Alu (UMW704-05)

☐ 1° Alu (UMW704-1)

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

### Shocks

**Front**

Piston: \_\_\_\_\_

Oil: # \_\_\_\_\_ #

Spring: \_\_\_\_\_

Limiters: In \_\_\_\_\_ mm In \_\_\_\_\_ mm

Out \_\_\_\_\_ mm Out \_\_\_\_\_ mm


Length (A): \_\_\_\_\_ mm

O-Ring: \_\_\_\_\_

Shock Top Type: ☐ Alu (UM719/Std) ☐ UM753-1

Ball End Type: Front ☐ S ☐ M ☐ L

Rear ☐ S ☐ M ☐ L



### Battery placement

Front

\_\_\_\_\_

\_\_\_\_\_

### Chassis

☐ Stock ☐ UM731

F \_\_\_\_\_ mm Ride Height R \_\_\_\_\_ mm

### Transmission

☐ Rear Motor

☐ Mid-Ship 3 Gear

☐ Mid-Ship 4 Gear

☐ Mid-Ship Laydown

### Battery Type

☐ Straight

☐ Separate

☐ Short

Type \_\_\_\_\_

### Track Condition

☐ Smooth

☐ Bumpy

☐ Low Traction

☐ Med. Traction

☐ High Traction

☐ Wet

☐ Dry

☐ Sandy

☐ Soft Dirt

☐ Grass

☐ Blue Groove

☐ Clay

☐ Dusty

☐ \_\_\_\_\_

### Wing

Wing Mount: ☐ Narrow ☐ Wide

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

☐ Blast-S

☐ Blast-L

☐ Step-S

☐ Step-M

☐ Step-L

☐ Step 2.0

☐ Step 3.0

☐ Straight Lip: ☐ Round

### Tire

Front

Tire \_\_\_\_\_

Insert \_\_\_\_\_

Wheel \_\_\_\_\_

Rear

Tire \_\_\_\_\_

Insert \_\_\_\_\_

Wheel \_\_\_\_\_

### Other

Motor: \_\_\_\_\_

ESC: \_\_\_\_\_

Ratio: \_\_\_\_\_