

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Shock Tower: _____

Toe: In Out _____ °

Toe Rod: _____

Front Bulkhead Weight Placement:

- None
- Bulkhead Inside _____ oz _____ g
- On the skid plate _____ oz _____ g (*1oz = 28g)

4.8mm Ball Stud:

- UM128 (Std)
- UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Caster:

- 25°
- 30°

Caster Block:

- 0.5
- 1.0
- None
- 0°
- 2°
- 4°

Spacer:

- A (UM502)
- B (UMW721/Std)
- C (UM567)
- B (UMW722/Brass)
- B (UMW723/Alu)

AI Steering Support:

- None
- UMW724

4.8mm Ball Stud:

- LA246 (-1mm Low Mount)
- 97050M (STD)

Ackermann Steer Spacer: _____ mm

- UMW701 Aluminum ST Plate
- UMW702 Aluminum Crank Arm

Wheel Hub:

- UM569/Std
- UM506

Wheelbase: F _____ mm R _____ mm

Comments: _____

Rear Suspension

Shock Position: Front Rear

Shock Tower: _____

RR: _____

Mid: _____

Susp Holder Spacer:

- F 0.5 1.0 None
- R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud:

- UM129
- UMW508 (+2mm High Mount)
- 97050M
- UM128 (Std)

Upper Spacer: _____ mm

Lower Susp Holder:

- Plastic RF RF2L RF2
- Option UMW511GM (RF/Alu)
- (Opt/Adjustable) UMW705 (RF/Alu) _____ Block
- UMW725 (RF-MID/Bra) _____ Block
- (Opt/Adjustable) UMW706 (RR-RWD) _____ Block
- UMW707 (RR-MID) _____ Block

Universal Swing Shaft: _____

Camber: _____ °

Rear Hub Carrier:

- 0° Type-B (UM519)
- 0° Type-B2 (UM519-2)
- 0° Type-B2 (UM519-2)
- 0.5° Alu (UMW704-05)
- 1° Alu (UMW704-1)

Drive Hub:

- 4mm (TFW113)
- 4.5mm (LAW30GM/Std.)
- 5.2mm (UMW523)

Axle Spacer:

- Out _____ mm
- In _____ mm

Sway Bar: None _____ mm

Wheelbase: F _____ mm R _____ mm

Comments: _____

Shocks

	Front	Rear
Piston:	_____	_____
Oil:	# _____	# _____
Spring:	_____	_____
Limiters:	In _____ mm	In _____ mm
	Out _____ mm	Out _____ mm
Length (A):	_____ mm	_____ mm
O-Ring:	_____	_____
Shock Top Type:	<input type="checkbox"/> Alu (UM719/Std)	<input type="checkbox"/> UM753-1
Ball End Type:	Front <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Battery placement

Front _____

Rear _____

Chassis

Stock UM731

F _____ mm Ride Height R _____ mm

Differential

Gear: _____

Ball: _____

Transmission

- Rear Motor
- Mid-Ship 3 Gear
- Mid-Ship 4 Gear
- Mid-Ship Laydown

Battery Type

- Straight
- Separate
- Short

Type _____

Track Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groove
- Clay
- Dusty

Wing

Wing Mount: Narrow Wide

Wing Angle: 4° 7° 10°

Blast-S Blast-L

Step-S Step-M Step-L

Step 2.0 Step 3.0

Straight Lip Round

Tire

Front _____ Rear _____

Tire _____

Insert _____

Wheel _____

Other

Motor: _____

ESC: _____

Ratio: _____