

Name: Karlos Date: 6.11.16 Track / City: Workshop Event: Rd 3 Winter Series

Front Suspension

Upper Spacer: 3mm mm

Shock Tower: Std

Toe: In Out 0°

Toe Rod: _____

Front Bulkhead Weight Placement:

None

Bulkhead Inside _____ oz _____ g

On the skid plate _____ oz _____ g (*1oz = 28g)

4.8mm Ball Stud: UM128 (Std) UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: 1mm mm

Camber: -1°

AI Steering Support: None UMW724

Axel Spacer: Out _____ mm In _____ mm

Wheel Hub: UMS69/Std UMS06

Caster Block Position: In (Wide/Std) Out (Narrow)

Caster Block: 0.5 0° 1.0 2° None 4°

Caster: 25° 30°

Spacer: A (UM502) B (UMW722/Brass) B (UMW723/Alu) C (UM567)

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Upper Spacer: 3 mm

RR: Mid:

Lower Susp Holder: Plastic RF RF2L RF2 Option UMW511GM (RF/Alu)

(Opt/Adjustable) UMW705 (RF/Alu) _____ Block UMW725 (RF-MID/Bra) ^{B version} _____ Block (Opt/Adjustable) UMW706 (RR-RWD) _____ Block UMW707 (RR-MID) ^{B version} _____ Block

Sway Bar: None _____ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (STD)

Ackermann Steer Spacer: 0 mm

UMW701 Aluminum ST Plate UMW702 Aluminum Crank Arm

Bump Steer Spacer: 1 mm

Axel Height Spacer: .5 mm 1 mm

Wheelbase: F 0 mm R 1 mm

Comments: Use Long Ball Stud inner Top Link with 3mm

Rear Suspension

Shock Position: Front Rear

Shock Tower: _____

Anti-Squat: _____ °

Susp Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Upper Spacer: 1 mm

Wheelbase: F 2 mm R 2 mm

Wheelbase: F 2 mm R 0 mm

Comments: Alloy Rear 0Deg Hubs Rr Mounted Shocks on rear of tower (Rb6 style)

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Upper Spacer: 3 mm

RR: Mid:

Lower Susp Holder: Plastic RF RF2L RF2 Option UMW511GM (RF/Alu)

(Opt/Adjustable) UMW705 (RF/Alu) _____ Block UMW725 (RF-MID/Bra) ^{B version} _____ Block (Opt/Adjustable) UMW706 (RR-RWD) _____ Block UMW707 (RR-MID) ^{B version} _____ Block

Sway Bar: None _____ mm

Universal Swing Shaft: Std

Camber: -1°

Drive Hub: 4mm (TFW113) 4.5mm (LAW30GM/Std.) 5.2mm (UMW523)

Axle Spacer: Out _____ mm In _____ mm

Rear Hub Carrier: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Type-B2 (UM519-2) 0.5° Alu (UMW704-05) 1° Alu (UMW704-1)

Shocks

	Front	Rear
Piston:	<u>3 x 1.5</u>	<u>3 x 1.6</u>
Oil:	# <u>30wt Asso</u>	# <u>30wt Asso</u>
Spring:	<u>Asso White</u>	<u>Asso Green</u>
Limiters:	In _____ mm Out _____ mm	In _____ mm Out _____ mm
Length (A):	<u>20</u> mm	<u>26</u> mm
O-Ring:	<u>X - Red</u>	<u>X-Red</u>
Shock Top Type:	<input checked="" type="checkbox"/> Alu (UM719/Std) <input type="checkbox"/> UM753-1	
Ball End Type:	Front <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Rear <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L

Battery placement

Rear most position again waterfall bracket.

Transmission

Rear Motor

Mid-Ship 3 Gear

Mid-Ship 4 Gear

Mid-Ship Laydown

Chassis

Stock UM731

F 21 mm Ride Height R 22 mm

Battery Type

Straight

Separate

Short

Type: Orion 5000mah shorty

Track Condition

Smooth Sandy

Bumpy Soft Dirt

Low Traction Grass

Med. Traction Blue Groove

High Traction Clay

Wet Dusty

Dry Rubber Floor

Wing

Wing Mount: Narrow Wide

Wing Angle: 4° 7° 10°

Lip: Straight Round 15mm

Blast-S Blast-L

Step-S Step-M Step-L

Step 2.0 Step 3.0

Tire

	Front	Rear
Tire	<u>Mini Pin 2wd</u>	<u>Mini Pin 2</u>
Insert	<u>Slim Schy</u>	<u>Schy</u>
Wheel	<u>Kyosho</u>	<u>Kyosho</u>

Other

Motor: Orion Mag 7.5t

ESC: R10.1

Ratio: 76-25