

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Shock Tower: _____ mm

Upper Spacer: _____ mm

Toe: ☐ In ☐ Out _____ °

Toe Rod: _____ mm

Front Bulkhead Weight Placement:

☐ None

☐ Bulkhead Inside _____ oz _____ g

☐ On the skid plate _____ oz _____ g (*1oz = 28g)

4.8mm Ball Stud:

☐ UM128 (Std)

☐ UMW508 (+2mm High Mount)

Caster:

☐ 25° ☐ 30°

Spacer:

☐ A (UM502) ☐ B (UMW722/Brass) ☐ C (UM567)

☐ B (UMW721/Std) ☐ B (UMW723/Alu)

Caster Block:

☐ 0.5 ☐ 1.0 ☐ None

☐ 0° ☐ 2° ☐ 4°

Comments: _____

AI Steering Support:

☐ None ☐ UMW724

Axel Spacer:

☐ Out _____ mm ☐ In _____ mm

Wheel Hub:

☐ UM569/Std ☐ UM506

Caster Block Position:

☐ In (Wide/Std) ☐ Out (Narrow)

4.8mm Ball Stud:

☐ LA246 (-1mm Low Mount) ☐ 97050M (STD)

Ackermann Steer Spacer:

_____ mm

☐ UMW701 Aluminum ST Plate ☐ UMW702 Aluminum Crank Arm

Bump Steer Spacer:

_____ mm

Axel Height Spacer:

☐ _____ mm ☐ _____ mm

Wheelbase: F _____ mm R _____ mm

Rear Suspension

Shock Position:

☐ Front ☐ Rear

Shock Tower:

☐ 1 ☐ 2 ☐ 3 ☐ 4

RR:

☐ 1 ☐ 2 ☐ 3

Mid:

☐ 1 ☐ 2

Susp Holder Spacer:

F ☐ 0.5 ☐ 1.0 ☐ None

R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____ °

4.8mm Ball Stud:

☐ UM129 ☐ UMW508 (+2mm High Mount) ☐ 97050M ☐ UM128 (Std)

Upper Spacer: _____ mm

Lower Susp Holder:

Plastic ☐ RF ☐ RF2L ☐ RF2

Option ☐ UMW511GM (RF/Alu)

(Opt/Adjustable)

☐ UMW705 (RF/Alu) _____ Block

☐ UMW725 (RF-MID/Bra) _____ Block

(Opt/Adjustable)

☐ UMW706 (RR-RWD) _____ Block

☐ UMW707 (RR-MID) _____ Block

Universal Swing Shaft:

☐ Type-B (UM519) ☐ Type-B2 (UM519-2)

Camber: _____ °

Drive Hub:

☐ 4mm (TFW113) ☐ 4.5mm (LAW30GM/Std.) ☐ 5.2mm (UMW523)

Axe Spacer:

☐ Out _____ mm ☐ In _____ mm

Sway Bar: ☐ None ☐ _____ mm

Comments: _____

Upper Spacer: _____ mm

Wheelbase: F _____ mm R _____ mm

Wheelbase: F _____ mm R _____ mm


Differential

☐ Gear: _____

☐ Ball: _____

Shocks

	Front	Rear
Piston:	_____	_____
Oil:	# _____ #	_____
Spring:	_____	_____
Limiters:	In _____ mm Out _____ mm	In _____ mm Out _____ mm
Length (A):	_____ mm	_____ mm
O-Ring:	_____	_____
Shock Top Type:	☐ Alu (UM719/Std) ☐ UM753-1	
Ball End Type:	Front ☐ S ☐ M ☐ L	Rear ☐ S ☐ M ☐ L



Battery placement

Front

Chassis

☐ Stock ☐ UM731

F _____ mm Ride Height R _____ mm

Transmission

☐ Rear Motor

☐ Mid-Ship 3 Gear

☐ Mid-Ship 4 Gear

☐ Mid-Ship Laydown

Battery Type

☐ Straight

☐ Separate

☐ Short

Type _____

Track Condition

☐ Smooth ☐ Sandy

☐ Bumpy ☐ Soft Dirt

☐ Low Traction ☐ Grass

☐ Med. Traction ☐ Blue Groove

☐ High Traction ☐ Clay

☐ Wet ☐ Dusty

☐ Dry _____

Wing

Wing Mount: ☐ Narrow ☐ Wide

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

☐ Blast-S ☐ Blast-L

☐ Step-S ☐ Step-M

☐ Step-L ☐ Step 2.0

☐ Step 3.0

☐ Straight Lip: ☐ Round

Tire

	Front	Rear
Tire	_____	_____
Insert	_____	_____
Wheel	_____	_____

Other

Motor: _____

ESC: _____

Ratio: _____