

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Shock Tower: _____

Toe: In Out _____°

Tie Rod: _____

Front Bulkhead Weight Placement:

- None
- Bulkhead Inside _____ oz _____ g
- On the skid plate _____ oz _____ g * 1oz=28g

4.8mm Ball Stud: Camber: _____°

- UM128(Std.)
- UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Caster: _____°

- 25°
- 30°

Caster Block: _____

- 0.5
- 0°
- 1.0
- 2°
- None
- 4°

Spacer: _____

- A (UM502)
- B (UMW722/Brass)
- B (UMW723/Alu)
- C (UM567)

AL. Steering Support:

- None
- UMW724

4.8mm Ball Stud:

- LA246 (-1mm Low Mount)
- 97050M (Std)

Ackerman Steer Spacer: _____ mm

- UMW701 Aluminum ST Plate
- UMW702 Aluminum Clank Arm

Wheel Hub:

- UM569 / Std
- UM506

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Shock Tower: _____

RR: _____

Mid: _____

4.8mm Ball Stud:

- UM129
- UMW508 (+2mm High Mount)
- 97050M
- UM128(Std.)

Upper Spacer: _____ mm

Sus Holder Spacer:

F: 0.5 1.0 None

R: 0.5 1.0 None

Anti-Squat: _____°

Universal Swing Shaft: _____

Camber: _____°

Drive Hub :

- 4mm (TFW113)
- 4.5mm (LAW30GM/Std.)
- 5.2mm (UMW523)

Wheelbase: F: _____ mm R: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Sway Bar: None _____ mm

Lower Sus. Holder:

Plastic

- RF
- RF2L
- RF2

Option

- UMW511GM (RF/Alu)

(Opt/Adjustable)

- UMW705(RF/Alu) _____ Block
- UMW725(RF-MID/Bra) _____ Block

(Opt/Adjustable)

- UMW706(RR-RWD) _____ Block
- UMW707(RR-MID) _____ Block

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Diff.

- Gear Diff. # _____
- Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	<input type="checkbox"/> Alu(UM719/Std)	<input type="checkbox"/> UM753-1
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Battery Placement:

None Screw

Front: Rear:

Foam:

- Front
- Rear
- None

Transmission

- Rear Motor
- Mid-Ship 3 Gear
- Mid-Ship 4 Gear
- Mid-Ship Laydown

Chassis

Stock UM731

F: _____ mm Ride Height: R: _____ mm

Battery Type

- Straight
- Separate
- Short

Type: _____

Track Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groove
- Clay
- Dusty

Wing

Wing Mount : Narrow Wide

Wing Angle : 4° 7° 10°

Lip : _____

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Step 3.0
- Straight
- Round

Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____

Other

Motor: _____

ESC: _____

Pinion/Spur: _____