

Name: Kohta Akimoto Date: 2015/07/18 Truck / City: - Event: ストックコンバット向け

Front Suspension

Upper Spacer: 0 mm

4.8mm Ball Stud: Camber: 1.0°

UM128 (Std) LA246 (-1mm Low Mount)
 UMW508 (+2mm High Mount) 97050M (Std)

Axle Spacer: Out 2 mm In 1 mm

4.8mm Ball Stud Spacer: 1 mm

Wheel Hub: Std mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 1 mm

Toe: In Out 0.5°

Tie Rod: _____

Front Bulkhead Weight Placement:

None A (UM502) B (UM721/Std.) C (UM567)
 Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: 0.75mm 0.75mm

Wheelbase: F: 0 mm R: 1 mm

Comments: UMW701/702:アルミパーツ使用

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____°

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Sway Bar: None _____ mm

Universal Swing Shaft: 65.5mm 2本線

Camber: 1.0°

Upper Spacer: 2 mm

Wheelbase: F: 2 mm R: 2 mm

RR: Type-B (UM519) Type-B2 (UM519-2)

Wheelbase: F: 2 mm R: 0 mm

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Axle Spacer: Out _____ mm In 0.3 mm

Upper Spacer: 1 mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 Wide RF2 UMW514+UMW515

Comments: UMW705(OUT_B), UMW707(OUT_B)アルミサスホルダー

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # _____ Ball Diff.

Shock

Shock Piston: Front 4×1.3mm Rear 4×1.3mm

Shock Oil: # 400(京商) # 400(京商)

Shock Spring: Pink Gold

Limiters: in 0 mm out 0 mm in 0 mm out 0 mm

Shock Length(A): 21.0 mm 28.5 mm

Shock Length(B): _____ mm _____ mm

O-ring: ORG03X (クリア) ORG03X (クリア)

Ball End type: Front: S M L Rear: S M L

Battery Placement

○ None ● Screw

Front Rear

Foam: Front Rear None

Chassis

サイドガード・ネジ無

F 24.0 mm Ride Height: R 23.5 mm

Battery Type

Straight Separate Short (横積み)

Type: ORION4000

Other

Motor: ORION VST2X 17.5T

ESC: Muchomore FLETA PRO

Pinion/Spur: 32/69

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

Blast-S Wing Mount: Blast-L Narrow Step-S Wide Step-M Wing Angle: Step-L 4° Step 2.0 7° Step3.0(ストレート) 10° Lip: .5mm残し

Tire

Tire: Front T-720C Rear T-755CN Traction Compound or comment: _____

Inserts: PL Mold _____

Wheel: Standard Standard _____

Comment

UMW710, UMW712, UMW713 カーボンパーツ使用

UMW718 VVCアルミドライブギヤ

UMW705/707:アルミサスホルダー, UMW704-0:V2アルミハブ, UMW701アルミSTプレート

UMB03LW 軽量ボディ