

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

☐ UM128 (Std)

☐ UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer:

☐ Out _____ mm

☐ In _____ mm

Wheel Hub: _____ mm

4.8mm Ball Stud:

☐ LA246 (-1mm Low Mount)

☐ UM129 (Std)

Ackerman Steer Spacer: _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer:

☐ _____ mm

☐ _____ mm

Toe: ☐ In ☐ Out _____ °

Caster:

☐ 25°

☐ 30°

Spacer:

☐ 0.5

☐ 1.0

☐ None

Caster Block:

☐ 0°

☐ 2°

☐ 4°

Block position:

☐ IN

☐ OUT

Front Bulkhead Weight Placement:

☐ None

☐ Bulkhead Inside _____ oz _____ g

☐ On the skid plate _____ oz _____ g * 1oz=28g

Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Sus Holder Spacer:

F ☐ 0.5 ☐ 1.0 ☐ None

R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____ °

4.8mm Ball Stud:

☐ UM129 (Std)

☐ UMW508 (+2mm High Mount)

☐ 97050M

Sway Bar: ☐ None ☐ _____ mm

Camber: _____ °

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Rear Hub add Toe:

☐ 0° Type-B (UM519)

☐ 0° Type-B2 (UM519-2)

☐ 0° Alu (UMW516-0)

☐ 0.5° Alu (UMW516-05)

☐ 1° Alu (UMW516-1)

Axle Spacer:

☐ Out _____ mm

☐ In _____ mm

Lower Sus Holder:

Normal ☐ RF ☐ Aluminum(Opt)

Narrow ☐ RF ☐ UMW511+UMW512

Wide ☐ RF2 ☐ UMW514+UMW515

Motor Position

☐ Rear Motor

☐ Midship Motor

Diff.

☐ Gear Diff. # _____

☐ Ball Diff.

Comments: _____

Shock

Shock Piston: _____

Shock Oil: # _____

Shock Spring: _____

Limiters:

in out mm mm

Shock Length(A): _____ mm

Shock Length(B): _____ mm

Shock Length(C): _____ mm

Ball End type:

Front: ☐ S ☐ M ☐ L

Rear: ☐ S ☐ M ☐ L

Chassis

Screw:

Ride Height: F _____ mm R _____ mm

Battery Position

Battery Type:

☐ Straight

☐ Separate

☐ Short

Battery Placement:

☐ Front

☐ Rear

Truck Condition

☐ Smooth

☐ Bumpy

☐ Low Truction

☐ Med. Truction

☐ Higt Truction

☐ Wet

☐ Dry

☐ Sandy

☐ Soft Dirt

☐ Grass

☐ Blue Groove

☐ Clay

☐ Dusty

☐ Other

Wing

☐ Blast-S

☐ Blast-L

☐ Step-S

☐ Step-M

☐ Step-L

☐ Step 2.0

Wing Mount:

☐ Narrow

☐ Wide

Wing Angle:

☐ 4°

☐ 7°

☐ 10°

Lip: _____

Tire

Front

Rear

Tire: _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Comment
