

Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

**Upper Spacer:** \_\_\_\_\_ mm

**4.8mm Ball Stud: Camber:** \_\_\_\_\_ °

UM128 (Std)  UMW508 (+2mm High Mount)

**4.8mm Ball Stud Spacer:** \_\_\_\_\_ mm

**Axle Spacer:**  Out \_\_\_\_\_ mm  In \_\_\_\_\_ mm

**4.8mm Ball Stud:**  LA246 (-1mm Low Mount)  UM129 (Std)

**Ackerman Steer Spacer:** \_\_\_\_\_ mm

**Wheel Hub:** \_\_\_\_\_ mm

**Bump Steer Spacer:** \_\_\_\_\_ mm

**Axle Height Spacer:**  \_\_\_\_\_ mm  \_\_\_\_\_ mm

**Toe:**  In  Out \_\_\_\_\_ °

**Caster:**  25°  30°

**Spacer:**  0.5  1.0  None

**Caster Block:**  0°  2°  4°

**Block position:**  IN  OUT

**Front Bulkhead Weight Placement:**

None

Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g

On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

### Rear Suspension

**Sus Holder Spacer:** F  0.5  1.0  None R  0.5  1.0  None

**Anti-Squat:** \_\_\_\_\_ °

**4.8mm Ball Stud:**  UM129 (Std)  UMW508 (+2mm High Mount)  97050M

**Sway Bar:**  None  \_\_\_\_\_ mm

**Camber:** \_\_\_\_\_ °

**Upper Spacer:** \_\_\_\_\_ mm

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**RR:** \_\_\_\_\_ mm

**Mid:** \_\_\_\_\_ mm

**Lower Sus Holder:** Normal  RF  Aluminum(Opt)  UMW511+UMW512  UMW514+UMW515

**Wide:**  RF2

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**Rear Hub add Toe:**  0°Type-B (UM519)  0°Type-B2 (UM519-2)  0°Alu (UMW516-0)  0.5°Alu (UMW516-05)  1°Alu (UMW516-1)

**Axle Spacer:**  Out \_\_\_\_\_ mm  In \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

### Motor Position

- Rear Motor
- Midship Motor

### Diff.

- Gear Diff. # \_\_\_\_\_
- Ball Diff.

### Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Length(B):	_____ mm	_____ mm
Shock Length(C):	_____ mm	_____ mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

### Chassis

**Screw:** \_\_\_\_\_

**Ride Height:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

### Battery Position

- Battery Type:**
- Straight
- Separate
- Short
- Battery Placement:**
- Front
- Rear

### Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

### Electronics

Motor: \_\_\_\_\_

Pinion/Spur: \_\_\_\_\_

Battery: \_\_\_\_\_

ESC: \_\_\_\_\_

### Truck Condition

- Smooth  Sandy
- Bumpy  Soft Dirt
- Low Truction  Grass
- Med. Truction  Blue Groove
- Higt Truction  Clay
- Wet  Dusty
- Dry  Other

### Wing

- Blast-S  Wing Mount: \_\_\_\_\_
- Blast-L  Narrow
- Step-S  Wide
- Step-M  Wing Angle: \_\_\_\_\_
- Step-L  4°
- Step 2.0  7°
- 10°
- Lip: \_\_\_\_\_

### Comment

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_