

Name: David Poulter Date: 17th February 2013 Truck / City: Stotfold Event: Winter Series Round 5

Front Suspension

4.8mm Ball Stud: Camber: -1.0°
 UM128 (Std)
 UMW508 (+2mm High Mount)

Upper Spacer: 2.0 mm
 4.8mm Ball Stud Spacer: 0.5 mm
 Axle Spacer: Out 1.0 mm In 2.0 mm
 Wheel Hub: _____ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)
 Ackerman Steer Spacer: 0.0 mm
 Bump Steer Spacer: 1.0 mm

Toe: In Out 0.0°
 Caster: 25° 30°
 Spacer: 0.5 1.0 None
 Caster Block: 0° 2° 4°
 Block position: IN OUT
 Axle Height Spacer: 0.5 mm 1.0 mm

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz _____ g
 On the skid plate _____ oz _____ g * 1oz=28g

Comments: Ali steering rack
 Wheelbase: F: 0.0 mm R: 1.0 mm

Rear Suspension

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °
 Sway Bar: None _____ mm
 Camber: -1.0°

Upper Spacer: 2.0 mm
 Wheelbase: F: 2.0 mm R: 2.0 mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M
 RR: Upper Spacer: 2.0 mm
 Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512
 Wide RF2 UMW514+UMW515

Wheelbase: F: 2.0 mm R: 0.0 mm
 Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Comments: Ali front hanger and plastic rear

Shock

	Front	Rear
Shock Piston:	<u>Kit 5 hole</u>	<u>Kit 5 hole</u>
Shock Oil:	<u>#550</u>	<u>#300</u>
Shock Spring:	<u>Red</u>	<u>Gold</u>
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Length(B):	<u>20.0</u> mm	<u>26.5</u> mm
Shock Length(C):	<u>6.0</u> mm	<u>9.0</u> mm
Ball End type:	Front: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	

Chassis

Slipper = Just looser than end of shaft
 Screw: _____

Ride Height: F 19 mm R 20 mm

Battery Position

Battery Type:
 Straight
 Separate
 Short

Battery Placement:
 Front
 Rear

Truck Condition

Smooth
 Bumpy
 Low Traction
 Med. Traction
 High Traction
 Wet
 Dry

Sandy
 Soft Dirt
 Grass
 Blue Groove
 Clay
 Dusty
 Other

Wing

Blast-S
 Blast-L
 Step-S
 Step-M
 Step-L
 Step 2.0
 Lip: LMR

Wing Mount: Narrow Wide
 Wing Angle: 4° 7° 10°

Tire

	Front	Rear
Tire:	<u>Sch LP Cut Stagger</u>	<u>Sch Minispike</u>
Inserts:	<u>None</u>	<u>Mr O - Blue</u>
Wheel:	<u>Kyosho Narrow</u>	<u>Kyosho</u>
Traction Compound:	<u>F=Yellow - R=Yellow</u>	

Electronics

Motor: Orion VST 7.5
 Pinion/Spur: 24/76
 Battery: Orion 5500
 ESC: Orion R10

Comment

Qualified 1st and finished 3rd after making a few errors.