

Name David Ronnefalk Date 20.10.2012 Truck / City VBC Borås Event VBC

Front Suspension

Upper Spacer: 1 mm

4.8mm Ball Stud: Camber: 1°

UM128 (Std)
 UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: 0.5 mm

Axle Spacer: Out 1 mm
 In _____ mm

Wheel Hub: 0 mm

4.8mm Ball Stud: LA246 (-1mm Low Mount)
 UM129 (Std)

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 1 mm

Toe: In Out 0°

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz _____ g
 On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30°
 A (UM502) B (UM721/Std.) C (UM567)

Spacer: 0.5 1.0 None
Caster Block: 0° 2° 4°
Block position: IN OUT

Axle Height Spacer: _____ mm 1.5 mm

Wheelbase: F: _____ mm R: 1 mm

Comments: _____

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____°

Upper Spacer: 2 mm

4.8mm Ball Stud: UM129 (Std)
 UMW508 (+2mm High Mount)
 97050M

Sway Bar: None _____ mm

Camber: 2°

Wheelbase: F: _____ mm R: 4 mm

RR: Upper Spacer: 0 mm

Mid: Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512
Wide RF2 UMW514+UMW515

Wheelbase: F: _____ mm R: _____ mm

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2)
 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Axle Spacer: Out _____ mm In _____ mm

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # 4000 Ball Diff.

Comments: 2mm washer behind sus.arm

Shock

	Front	Rear
Shock Piston:	<u>2x1.4Ghea</u>	<u>2x1.4Ghea</u>
Shock Oil:	<u>#27.5 Losi</u>	<u>#22.5 Losi</u>
Shock Spring:	<u>Red</u>	<u>Red</u>
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Length(B):	<u>19</u> mm	<u>26</u> mm
Shock Length(C):	_____ mm	_____ mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L

Chassis

Screw:

Ride Height: F 21 mm R 21 mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Truck Condition

Smooth Sandy
 Bumpy Soft Dirt
 Low Truction Grass
 Med. Truction Blue Groove
 Higt Truction Clay
 Wet Dusty
 Dry Other

Wing

Blast-S Wing Mount :
 Blast-L Narrow
 Step-S Wide
 Step-M Wing Angle :
 Step-L 4°
 Step 2.0 7°
 10°
Lip : _____

Tire

	Front	Rear
Tire:	<u>VBC Slick</u>	<u>VBC Slick</u>
Inserts:	<u>PL Std</u>	<u>AKA Red</u>
Wheel:	<u>AKA 1/10</u>	<u>AKA 1/10</u>
Traction Compound:	_____	_____

Electronics

Motor: Orion 7.5
Pinion/Spur: 23
Battery: Orion Saddle
ESC: Orion R10Pro

Comment
