

Name: Dean Vuckovich Date: 10/30/2012 Truck / City: Outdoor Event: Club Racing

Front Suspension

4.8mm Ball Stud: Camber: -1°

UM128 (Std) UMW508 (+2mm High Mount)

Upper Spacer: 1.5 mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Axle Spacer: Out 1.0 mm In 2.0 mm

Ackerman Steer Spacer: 0 mm

4.8mm Ball Stud Spacer: 0 mm

Wheel Hub: mm

Bump Steer Spacer: 2.5 mm

Toe: In Out 0°

Front Bulkhead Weight Placement: None Bulkhead Inside oz g On the skid plate oz g * 1oz=28g

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Axle Height Spacer: 0 mm 1.5 mm

Wheelbase: F: 0 mm R: 1 mm

Comments:

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: 0°

Upper Spacer: 2 mm

Wheelbase: F: 2 mm R: 2 mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None mm

Camber: -1°

Wheelbase: F: 2 mm R: 0 mm

Rear Hub add Toe: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW516-0) 0.5° Alu (UMW516-05) 1° Alu (UMW516-1)

Axle Spacer: Out 0.0 mm In 0.3 mm

RR: mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 UMW514+UMW515

Narrow Wide RF2

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # Ball Diff.

Comments:

Shock

	Front	Rear
Shock Piston:	<u>Std - 5 Hole</u>	<u>Std - 5 Hole</u>
Shock Oil:	<u>#37.5 Losi</u>	<u>#32.5 Losi</u>
Shock Spring:	<u>Pink</u>	<u>Gold</u>
Limiters:	in <u> </u> mm out <u> </u> mm	in <u> </u> mm out <u> </u> mm
Shock Length(A):	<u> </u> mm	<u> </u> mm
Shock Length(B):	<u>19.5</u> mm	<u>27.0</u> mm
Shock Length(C):	<u> </u> mm	<u> </u> mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L <input checked="" type="checkbox"/> L

Chassis

Screw:

Ride Height: F 24.0 mm R 23.5 mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Truck Condition

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Truaction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Truaction	<input type="checkbox"/> Blue Groove
<input type="checkbox"/> Higt Truaction	<input type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

Wing

Blast-S Wing Mount : Blast-L Narrow Step-S Wide Step-M Wing Angle : Step-L 4° Step 2.0 7° 10°

Lip :

Tire

	Front	Rear
Tire:	<u> </u>	<u> </u>
Inserts:	<u> </u>	<u> </u>
Wheel:	<u> </u>	<u> </u>
Traction Compound:	<u> </u>	<u> </u>

Electronics

Motor: Novak 17.5

Pinion/Spur: 29/69

Battery: GA 4200 60C

ESC: Novak GTB2

Comment