

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm
Front Tower: ☐ Std ☐ Carbon
Toe: ☐ In ☐ Out _____°
Tie Rod: _____
Front Bulkhead Weight Placement:
☐ None
☐ Bulkhead Inside _____ oz _____ g
☐ On the skid plate _____ oz _____ g * 1oz=28g

4.8mm Ball Stud:
☐ UM128(Std)
☐ UMW508(+2mm High Mount)
4.8mm Ball Stud Spacer: _____ mm
Caster: ☐ 25° ☐ 30°
☐ A (UM502)
☐ B (UM721/Std.)
☐ C (UM567)
Spacer: ☐ 0.5 ☐ 1.0 ☐ None
Caster Block: ☐ 0° ☐ 2° ☐ 4°
Front Arm: ☐ Std ☐ Carbon

Camber: _____°
Forward(Std)
☐ Reverse
4.8mm Ball Stud:
☐ LA246 (-1mm Low Mount)
☐ 97050M (Std)
Ackerman Steer Spacer: _____ mm
C Hub: ☐ Std ☐ Carbon
Knuckle: ☐ Std ☐ Carbon
Bump Steer Spacer: _____ mm
Wheel Hub: _____ mm
Front Axle:
☐ UM569 (Std)
☐ UM506 (RB5)
Caster Block position:
☐ IN (wide/Std)
☐ OUT (Narrow)
Axle Height Spacer: _____ mm
Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Rear Tower: ☐ Std ☐ Carbon
4.8mm Ball Stud:
☐ UM129
☐ UMW508(+2 High mount)
☐ 97050M
☐ UM128(Std)
RR: _____ mm
Upper Spacer: _____ mm
Lower Sus Holder:
 Normal ☐ RF ☐ UMW511+UMW512 ☐ RM UMW705/706
 Wide ☐ RF2 ☐ UMW514+UMW515 ☐ MM UMW705/707
Sus Holder Spacer:
 F ☐ 0.5 ☐ 1.0 ☐ None
 R ☐ 0.5 ☐ 1.0 ☐ None
Anti-Squat: _____°
Sway Bar: ☐ None ☐ _____ mm
Universal Swing Shaft: _____ mm
Camber: _____°
Axle Spacer: ☐ Out _____ mm ☐ In _____ mm
Upper Spacer: _____ mm
Hub spacing: F: _____ mm R: _____ mm
Outer Bearing: ☐ 5X10 ☐ 5X11 ☐ 5X13
Wheelbase(arm): F: _____ mm R: _____ mm
Rear Arm:
☐ UM713(Std)
☐ UM521/566
☐ UM521-1
☐ UM503(Short)
☐ UMW711(Carbon)
Rear Hub Toe:
☐ 0° Type-B(UM519Std)
☐ 0° Type-B2(UM519-2)
☐ 0° Alu (UMW704-0)
☐ 0.5° Alu (UMW704-05)
☐ 1° Alu (UMW704-1)
Motor Position:
☐ Rear Motor
☐ Midship Motor
Diff.:
☐ Gear Diff. # _____
☐ Ball Diff.
Comments: _____

Shock

Front **Rear**

Shock Piston: _____

Shock Oil: # _____ # _____

Shock Spring: _____

Limiters: in out mm in out mm mm

Shock Length(A): _____ mm _____ mm

Shock Length(B): _____ mm _____ mm

O-ring: _____

Ball End type: Front: ☐ S ☐ M ☐ L ☐ R
 Rear: ☐ S ☐ M ☐ L ☐ R

Shock Cap: ☐ UM719(Std) ☐ UM753-1(Bleeder)

Battery Placement:

☐ UM787 ☐ None ☐ Screw

Comments: _____

Front **Rear**

Foam: ☐ Front ☐ Rear ☐ None

Chassis

☐ UM700(Std) ☐ UMW720(Lightweight)

F _____ mm **Ride Height:** **R** _____ mm

Battery Type

☐ Straight
☐ Saddle
☐ Short
Type: _____

Other

Motor: _____
ESC: _____
Pinion/Spur: _____

Tire

Front **Rear** **Traction Compound and/or comments:**

Tire: _____

Inserts: _____

Wheel: _____

Comments:

Track Condition

☐ Smooth ☐ Sandy
☐ Bumpy ☐ Soft Dirt
☐ Low Bite ☐ Grass
☐ Med. Bite ☐ Blue Groove
☐ High Bite ☐ Clay
☐ Wet ☐ Dusty
☐ Dry ☐ Other

Body&Wing

☐ UMB03
☐ UMB03LW
Wing Mount : ☐ Narrow ☐ Wide
Wing Angle : ☐ 4° ☐ 7° ☐ 10°
☐ Blast-S
☐ Blast-L
☐ Step-S
☐ Step-M
☐ Step-L
☐ Step 2.0
Lip : _____