

Name: Jared Tebo Date: August 2013 Truck / City: A-Main / Silver Dollar Event: ROAR Nationals

### Front Suspension

4.8mm Ball Stud:  UM128 (Std)  UMW508 (+2mm High Mount)

Camber: 2°

Upper Spacer: 1 mm

4.8mm Ball Stud Spacer: 1 mm

Axle Spacer:  Out      mm  In      mm

Wheel Hub:      mm

4.8mm Ball Stud:  LA246 (-1mm Low Mount)  97050M (Std)

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 2 mm

Toe:  In  Out 1°

Tie Rod:     

Front Bulkhead Weight Placement:  None  Bulkhead Inside      oz      g  On the skid plate      oz      g \* 1oz=28g

Caster:  25°  30°  A (UM502)  B (UM721/Std.)  C (UM567)

Spacer:  0.5  1.0  None

Caster Block:  0°  2°  4°

Caster Block position:  IN (wide/Std)  OUT (Narrow)

Axle Height Spacer:  1 mm  .5 mm

Comments: Ackermann Turned Around Wheelbase: F:      mm R: 1 mm

### Rear Suspension

Sus Holder Spacer: F  0.5  1.0  None R  0.5  1.0  None

Anti-Squat:      °

4.8mm Ball Stud:  UM129  UMW508 (+2mm High Mount)  97050M  UM128 (Std)

Sway Bar:  None       mm

Upper Spacer: 2 mm

Wheelbase: F: 2 mm R:      mm

RR:  Type-B (UM519)  Type-B2 (UM519-2)

Universal Swing Shaft:       mm

Camber: 2°

Wheelbase: F:      mm R:      mm

Rear Hub add Toe:  0° Type-B (UM519)  0° Type-B2 (UM519-2)  0° Alu (UMW516-0)  0.5° Alu (UMW516-05)  1° Alu (UMW516-1)

Axle Spacer:  Out      mm  In      mm

Upper Spacer: 1 mm

Lower Sus Holder: Normal  RF  UMW511+UMW512  Aluminum(Opt)  UMW514+UMW515 Wide  RF2

Comments: UM521-1 Arms/UMW705-707 B-out/B-out

### Shock

Shock Piston: Front 4 X 55 Rear 4 X 55

Shock Oil: # 40 # 35

Shock Spring: Pink Gold

Limiters: in out mm mm in out mm mm

Shock Length(A):      mm      mm

Shock Length(B): 20 mm 27 mm

O-ring:     

Ball End type: Front: S  M  L  Rear: S  M  L

### Battery Placement:

None  Screw

Front Rear

Foam:  Front  Rear  None

### Battery Type

Straight  Separate  Short

Type: Orion 5500

### Chassis

F 23.5 mm Ride Height: R 22 mm

### Other

Motor: Orion 7.5

ESC: Orion R10 Pro

Pinion/Spur: 22/76

### Tire

Front Rear Traction Compound or comment:

Tire: PL Scrub PL Suburb

Inserts: AKA R AKA R

Wheel: Kyosho Kyosho

### Truck Condition

Smooth  Sandy  Bumpy  Soft Dirt  Low Traction  Grass  Med. Traction  Blue Groove  High Traction  Clay  Wet  Dusty  Dry  Other

### Wing

Blast-S  Blast-L  Step-S  Step-M  Step-L  Step 2.0

Wing Mount:  Narrow  Wide

Wing Angle:  4°  7°  10°

Lip:     

### Comment

Short Servo.